



























This list supersedes all previous lists.

**USA**

**MACHINE PRICES and SPECIFICATIONS**

Effective January 1, 2022

**FM-115 Front Mount 3pt  
Hitch Frame**

**FM-115 Specs:**

**Tractor HP:** Max. 115 hp (86kw)

**Tractor HP:** Min. 55hp(41kw) for SDX-840, 85hp (63kw)for SDX-102, RDX-102

**Tractor Hydraulic Requirement** - 3 remote circuits with a minimum total hydraulic output of 10 GPM at 1200 PSI rotating drum.  
 An additional circuit is required if the snow blower has a rotating drum (RDX-102).

**Tractor PTO** - 540 RPM

**Lift Capacity:** Maximum - 5000 lbs (1162 KG)

**Adjustability** - Fits tractors between 111-1/2" and 164-1/2" measured the front mount plate to the drawbar pin

**Normal Lift Range** - 18"

**Nominal Ground Clearance** - 10" depending on tractor installation

**Approximate Weight** - 1400 lbs (636 KG)

**~ ~ Selection 1 ~ Choose a Basic Unit ~ ~**

		<b>Retail Price</b>	<b>Weight (lbs)</b>
<b>F115-100</b>	FM-115 Front Mount Frame <i>(NO Driveline Package)</i>	6,541.00	750
<b>F115-200</b>	<i>Driveline package (Used for Snow Blowers)</i>	4,783.00	
<b>340-924WG</b>	1-3/8 Z6 (Size 9) for RDX-102	940.00	
	Assembly	Call for Pricing	

**\*\*\*Call for Current Steel Surcharge Amounts\*\*\***

\* Schulte Industries Ltd. reserves the right to adjust prices and/or surcharges at any time.  
 \* Prices subject to any applicable taxes.  
 \* Prices and surcharges are those in effect at time of shipment.