

MANUFACTURED BY
AG-MEIER IND. L.L.C.
(254) 939-3731
1-800-446-7319

MOHAWK

BRAVE



Domed Deck



Cutting Height
 Cutting Width
 Overall Width
 Overall Length
 Approx. Weight
 Blades
 Blade Carrier
 Blade Tip Speed (fpm)
 Max. Brush Size
 Gearbox HP
 Gearbox Protection
 Drive Line Size #
 Deck Thickness (Ga)
 Side Skirt Thickness (Ga)
 Side Skirt Depth
 Wheels
 Number of Wheels
 Hitch Type
 Tractor P.T.O. RPM
 Minimum HP Required
 Taper Splined Output Shaft Dia
 Safety Shield

	BRAVE 4	BRAVE 5	BRAVE 6	BRAVE 7
Cutting Height	1"-15"	1"-15"	1"-15"	1"-15"
Cutting Width	48"	60"	72"	82-1/2"
Overall Width	53-3/4"	66-1/2"	79"	85-1/2"
Overall Length	75"	96"	110"	120"
Approx. Weight	460 lbs.	555 lbs.	645 lbs.	1,055 lbs.
Blades	1/2" x 3-1/2"	1/2" x 3-1/2"	1/2" x 3-1/2"	1/2" x 3-1/2"
Blade Carrier	Dish	Dish	Dish	Dish
Blade Tip Speed (fpm)	9,992	12,490	14,989	14,394
Max. Brush Size	1-1/2"	1-1/2"	1-1/2"	2"
Gearbox HP	45	45	45	80
Gearbox Protection	Shear Pin (Slip Clutch Optional)			Slip Clutch
Drive Line Size #	ASAE Cat. IV	ASAE Cat. IV	ASAE Cat. IV	ASAE Cat. VI
Deck Thickness (Ga)	11	11	11	10
Side Skirt Thickness (Ga)	11	11	11	7
Side Skirt Depth	7	7"	7"	8"
Wheels	Semi-Pneumatic	Laminated Tires	Laminated Tires	Laminated Tires
Number of Wheels	1	1	1	2
Hitch Type	3 Pt., Cat. I	3 Pt., Cat. I	3 Pt., Cat. I	3-Point, Cat II
Tractor P.T.O. RPM	540	540	540	540
Minimum HP Required	20	25	30	40
Taper Splined Output Shaft Dia	1-5/8"	1-5/8"	1-5/8"	2"
Safety Shield	Rubber Deflectors			

AG-MEIER IND. L.L.C. • 920 East 6th Ave. • Belton, TX 76513
 (254) 939-3731 • 1-800-446-7319