

QUALITY PRODUCTS FOR YOUR LAND, FROM BRANDS YOU LOVE!



## SUGGESTED RETAIL PRICEBOOK JULY 2025

NOTE: DUE TO MANUFACTURER TRADE AGREEMENTS, SOME PRODUCTS MIGHT NOT BE AVAILABLE IN CERTAIN AREAS. PLEASE CHECK WITH YOUR TERRITORY REPRESENTATIVE FOR MORE DETAILS.

# **DEALER RESOURCES**

SALES									
Email:	sales@br-equipment.com (general inquiries) orders@br-equipment.com (place whole goods orders via email)								
Phone:	(252) 822-7140 Option 1								
Fax:	(252) 787-5855								
	ACCOUNTING								
Email:	accounts@br-equipment.com								
Direct Phone:	(252) 822-7140 Option 4								
Fax:	(252) 787-5855								
	PARTS								
Email:	parts@br-equipment.com (inquiry and place parts orders)								
Direct Phone:	(252) 822-7140 Option 2								
Fax:	(252) 787-5855								
	WARRANTY/SERVICE								
Email:	service@br-equipment.com warranty@br-equipment.com								
Direct Phone:	(252) 822-7140 Option 3								
Fax:	(252) 787-5855								
	SHIPPING								
Email:	shipping@br-equipment.com (freight quotes, tracking, shipping issues)								
Direct Phone:	(252) 316-2121 (252) 557-4822								
	MANUALS & BROCHURES								
Website	www.br-equipment.com								
	ONLINE DEALER ACCESS								
Login Information	See your Sales Representative								
What you can access here:	<ul> <li>Whole goods Order Forms</li> <li>Parts Order Forms</li> <li>Brochure Request Forms</li> <li>Warranty Registration Forms</li> <li>Warranty Claim Forms</li> </ul>								

# CONTENTS BY MANUFACTURER



DIAMOND DISCOUNT STRUCTURE

	BALER-MINI ROUND	32
	BALE UNROLLER	57
	BELT RAKE	25
	BOX BLADES	80-81
	CHAIN AND PASTURE HARROWS	58-60
	CULTIPACKER	77
A R	CONVENTIONAL DRILL (CROP-SEEDER)	44-45
	CORN/SOYBEAN PLANTER	51
	CRIMPER	56
	DISC HARROWS	76
	DISC HARROW WITH SEEDER	50
	DISC MOWERS	6-7
RIVE	DITCH BANK MOWERS	64
	DRILL-NO TILL	46-49
	DRUM MOWERS	12
	FINISHING MOWERS	61
	FLAIL MOWERS	62,64
	HAY TEDDER	16-19
3	HAY RAKE (POWER RAKE)	29
5	LAND LEVELER	82-83
	LANDSCAPE RAKES	74
	POST HOLE DIGGER	90
	REAR BLADES	75
	ROTARY CUTTERS	67-69
	ROTARY RAKES	22,24
<	ROTARY TILLERS	
	SUB-COMPACT (DLT SERIES)	38
	COMPACT (TXG SERIES)	39
2	MEDIUM-DUTY (YCT SERIES)	40
	MEDIUM-DUTY REVERSE ROTATION	41
	HEAVY DUTY (RXT SERIES)	42
	MULTI-SPEED GEARBOX (CXT)	43
U U	SHANK CULTIVATOR	78
	SPREADERS	
	3 POINT	71
	PULL-TYPE	71
	COMPACT SIDE SHOT	70
	PENDULAR	73
		79,91-92
	WOOD CHIPPERS	
		84-85
	DITCHBANK FLAIL MOWER	65
$\mathbf{J} \supset \mathbf{Z}$		63
FORZA		86-89

	ADAPTER BRACKETS	117
	ADAPTER BRACKETS BALE GRABBERS	99
	BALE SPEARS	98
	BALE UNWINDER	99
	BRUSH CUTTERS (SKID LOADER)	
		111
	HEAVY DUTY	111
	SERIOUS DUTY BUCKETS	112
		100
	BEAST SERIES	
	COMPACT UTILITY	100
		102
		101
	ROCK BUCKET	102
ATTACHMEN	SERIOUS DUTY	101
3.	GRAPPLES	
	UTILITY ROOT GRAPPLES	104
	COMMERCIAL ROOT GRAPPLES	105
$\mathbf{Y}$	CLAW GRAPPLES	106-107
	UTILITY ROOT GRAPPLES COMMERCIAL ROOT GRAPPLES CLAW GRAPPLES CLAW GRAPPLE FORK GRAPPLE GRAPPLE GRAPPLE BUCKET LAND DLANE	103
	FORK GRAPPLE	108
	GRAPPLE BUCKET	108
Zį		110
	MANURE FORKS	118
S	MINI SKID STEER ATTACHMENTS	119-120
	PALLET FORKS	
	SUB-COMPACT	95-96
	COMPACT	95-96
	MEDIUM DUTY	95-96
	HEAVY DUTY	95-96
	HYDRAULIC	97
	WALK-THRU	97
	STUMP BUCKETS & GRAPPLES	113-114
	TRAILER MOVER	118
	VIBRATORY POST DRIVER	109
	QUICK-ATTACH PLATES	117
	SNOW REMOVAL	115-116
	TOOTH BARS	117

STAR DISCOUNT STRUCTURE

	DELTA HARROWS	CHAIN HARROWS	60
DIAMOND DISCOUNT		SINGLE BALE WRAPPERS	
STRUCTURE	ECONO-WRAP	STATIONARY	33
		SELF-LOADING	34-35
		BALE WRAPPER (SELF-LOADING )	36
		DISC MOWER	8-9
		DISC MOWER WITH CONDITIONER	10-11
		SICKLEBAR MOWER	13
	T Z	HAY TEDDERS	14-15
	Ō	HAY RAKES	
DIAMOND	RC	CARTED WHEEL RAKE	27
DISCOUNT STRUCTURE	ROSSI	BAT RAKE	28
		MAXIMUS RAKE	30
		EASY RAKE	31
		THREE POINT WHEEL RAKE	26
		TEDDER RAKE	23
		ROTARY RAKE	20-21
		CONSERVATION SEEDER	54-55
	GREENSCAPE	FOOD PLOTTER (NO-TILL DRILL)	52-53
STAR DISCOUNT STRUCTURE		LIFT-SAFE IMPLEMENT HANDLER	121
	KEMCO	INLINE BALE WRAPPER	37

## **Disc Mower**

Available in 3 popular sizes, the Tar River side-mounted Disc Mower is built strong to stand up to years of rough conditions, giving you an excellent, quality cut. The reinforced A-frame made of heavy square tubing with Category II & III three-point hitch and the durable compensation spring ensure stability and durability during work.

The V-Belt and Shear-Hub systems protect the cutter-bar in the case of hitting obstacles. The break-away system provides additional protection to the cutter-bar by allowing it to pivot backwards when it encounters an obstruction. Simply back the tractor up and the break-away bar and mower will reset into the working position.

The cutter bar is designed for quick and easy replacement of each of the individual cutting units, which eliminates the need to take apart the entire cutter-bar for most repairs.

Models available: 5,6 and 7 disc configurations.



## **Specifications:**

- PTO Shaft 460 Nm
- Heavy Cutter bar with SAFETY DEVICE SYSTEM
- Protective Barriers made of a Bent Pipe Profile
- Protective Apron—reinforced with a rubber collar
- Cat. 2 and 3

- Quick Blade Change System
- Spring-based relief system
- Adjustable lower hitch pins
- o Break-Away System
- 2 Year Limited Warranty on cutter bar



## **MOWER FEATURES**



◊ 0" - 8" range of terrain following

Quick Blade Change System

**CUTTING BAR WITH SAFETY SHEAR-HUB** 

Shear Hub Protection for Heavy Cutter bar



Model	# of Discs	Blades per Disc	Working Width	HP	Weight (Ibs.)	List Price
DCM2083	5	2	6' 11"	30	1,096	\$10.500
DCM2098	6	2	8' 2"	45	1,162	\$10,950
DCM2110	7	2	9'2"	60	1,241	\$12,550

## Disc Mower



Available in 5 popular sizes, the Enorossi side-mounted Disc Mower is built strong to stand up to years of rough mowing conditions, giving you an excellent quality cut. The heavy duty A-frame with Category 1 & 2 three-point hitch and the strong compensation spring ensure stability and durability.

The V-Belt and Shear-Hub systems protect the cutter-bar in the case of obstacles. The break-away system provides additional protection to the cutter-bar by allowing it to pivot backwards when it encounters an obstruction. Simply back the tractor up and the break-away bar and mower will reset into the working position.

The cutter-bar is designed for quick and easy replacement of each of the individual cutting units, eliminating the need to take apart the entire cutter-bar for most repairs.

Models available: 4, 5, 6, 7, and 8 disc configurations; 3-blade discs available on 4, 6 and 8 disc models.







Disc conveyor bolted on top of guard support to avoid wrapping problems

Anti-wrapping support for heavy grass

Moves 90° for transport will cut at 35° up or down for hills, banks, terraces, etc.

## DIAMOND DISCOUNT STRUCTURE

## **Specifications:**

- ◊ "Sneak-A-Peek" belt tension viewer for less down time
- ◊ Compensation spring "break-away" system
- $\diamond$   $\$  Heavy Duty shield PTO shaft with overrunning clutch
- ◊ Hydraulic cylinder lift mechanism
- $\diamond$   $\;$  High blade tip speed for smooth, fast cutting efficiency
- ◊ 2 Year Limited Warranty on cutter bar



Easy changing hubs with 4-bolt disc cutting unit



Easily adjust belt tension without taking off outer cover





Individual Shear-hub System on cutter bar



Model	# of Discs	Blades Per Disc	Working Width	Lift	HP	РТО	Weight (Ibs.)	Ship Weight (Ibs.)	List Price
DM4	4	2	5'5"	Hydraulic	35	540 RPM	925	982	\$9,590
DM4 3C	4	3	5'5"	Hydraulic	35	540 RPM	931	986	\$9,730
DM5	5	2	6'7"	Hydraulic	40	540 RPM	1,015	1,070	\$10,820
DM6	6	2	8'	Hydraulic	50	540 RPM	1,103	1,158	\$11,980
DM6 3C	6	3	8'	Hydraulic	50	540 RPM	1,109	1,164	\$12,125
DM7	7	2	9'2"	Hydraulic	60	540 RPM	1,413	1,488	\$14,780
DM8	8	2	10'5"	Hydraulic	70	540 RPM	1,523	1,698	\$15,995
DM8 3C	8	3	10'5"	Hydraulic	70	540 RPM	1,532	1,707	\$15,995

## **Disc Mower with Conditioner**



The DM ROLL series offers the rubber roller conditioner to facilitate the drying of the grass. Its agile use makes it suitable for quick and safe work.

Offered in two sizes to meet every farm's need.



The DMC ROLL Mowers have two rear reflectors that adjust the swath width which can be minimum of 60 cm (2 ft.) or maximum of 120 cm (4 ft.)











#### Special Disc for Conditioner

The disc is more robust with a specific reinforcement that allows the launch of the product inside the ROLL rollers helping the work and therefore the forward speed.



#### **Gear Transmission**

The two rubber rollers are gear driven to provide continuous synchronization in the event of uneven flow of high-volume grasses.

Model	# of Discs	Blades Per Disc	Working Width	Lift	HP	РТО	Weight (Ibs.)	Ship Weight (Ibs.)	List Price
DMC 5 ROLL	5	2	7 ft.	Hyd.	80-90	540 rpm	1,760	2,030	\$19,910
DMC 6 3C ROLL	6	3	8 ft.	Hyd.	90-100	540 rpm	1,910	2,160	\$22,260

#### Drum Mover ( ) DIAMOND DIAMOND



Tar River Implements' Drum Mowers have very few moving parts, are low maintenance and have a heavy built A -frame. The Tar River Drum Mower is a great economic alternative to the Disc and Sickle bar mowers while still giving a good cut. The BDR Series Drum Mower can mow at high speeds and offers reliable mowing in all conditions, easily cutting through tall and thick grasses. Available in 4 popular sizes, Tar River Implements has a perfect fit for your small hay operation.

#### **Drum Mower Benefits:**

- Mow at High Speeds
- ◊ No Hydraulics Necessary
- Few Moving Parts & Easy Maintenance
- Great Alternative to Disc & Sickle bar Mowers for Small Hay Producers
- Easily Cuts Through Tall and Thick Grass
- Obsigned for Reliable Mowing in All Conditions

#### **BDR Series Drum Mower Features:**

- ♦ Heavy Duty A-frame
- 3 Blades per Drum (2 on the BDR-135 & 4 on BDR-210H)
- ♦ Compensation Spring "Break-Away" System
- $\Diamond$   $\$  High Blade Tip Speed for Smooth, Fast Cutting Efficiency
- ♦ V-Belt Drive
- Internal Overrunning Clutch
- Easy & Quick Blade Change

Model	# of Drums	Blades Per Drum	Category Hitch	Working Width	Min. Recommended Tractor Weight	Lift	Min HP	рто	Weight (Ibs.)	List Price
BDR-135	2	2	Cat. 1	4'5"	2,100 lbs.	Manual	20	540 RPM	661	\$3,925
BDR-165	2	3	Cat. 1 & 2	5'5"	2,600 lbs.	Manual	28	540 RPM	794	\$4,460
BDR-185	2	3	Cat. 1 & 2	6'1"	3,900 lbs.	Manual	35	540 RPM	893	\$4,995
BDR-210H	2	4	Cat. 2 & 3	6'9"	6,500 lbs.	Hyd.	65	540 RPM	1,240	\$7,950
BDR-A80	Hydraulic	: Lift Kit for E	3DR-165/185	5		<u>.</u>				\$670

# Sicklebar Mower 🔇



These double action Sickle Bar Mowers with an adjustable 3 point hitch ensure a sharp clean cut on any type of grass. The safety breakaway bar helps protect the cutter from obstructions in the field.





Safety breakaway bar

#### **Specifications:**

- Three Point Hitch Cat.1 & 2  $\Diamond$
- $\diamond$ Double Action cutter bar
- $\diamond$ Heavy duty shielded PTO shaft
- $\Diamond$ High quality powder-coat paint
- $\diamond$ Cuts at 90° up and 70° down
- $\Diamond$ Safety release
- $\diamond$ Ideal for hay or ditch bank mowing
- $\Diamond$ Extra cutting blade included

and the second second second							
Model	Working Width	Cutting Action	Min HP	Lift Type	Weight (Ibs.)	Ship Weight (Ibs.)	List Price
BFT 150	5'	Double	20	Select Kit	441	491	\$5,425+ Lift Kit
BFS 180	6'	Double	35	Select Kit	575	625	\$6,150+ Lift Kit
BFS 210	7'	Double	35	Select Kit	634	684	\$6,510+ Lift Kit
BFS 240H	8'	Double	50	Hydraulic	673	723	\$7,995
BFS 270H	9'	Double	50	Hydraulic	711	751	\$8,110
IANUAL AND H	YDRAULIC LIFT	KITS					
R0180-31500	Manual Lift Kit	for BFT 150					\$430
R0180-31344	Hydraulic Lift K	kit for BFT 150					\$640
R0173-10005	Manual Lift Kit	for BFS 180/210	)				\$430
R0180-31301	Hydraulic Lift K	Kit for BFS 180/2	10				\$640
ickle Bar Mowers	s are packaged 2	per crate (additi	ional cost if p	urchased indivi	idually)		\$100 net

## Hay Tedder



The Enorossi Vortex Hay Tedder comes in the 17', 19', 24', and 32' working widths. All units come standard with hydraulic lift, high-floatation 16" balloon tires, and fender hubs on the inside tires, Universal-Joint rotor style and a heavy 8"x4" rectangular -tube frame. The 19', 24', and 32' tedders come standard with hydraulic tilt.

The newest additions to the lineup are the Professional G6V 740PRO and G8V 980PRO. A 6 and 8 basket tedder with heavy transport frame allowing it to quickly fold up and speed from field to field.





U-Joint Engagement on Rotors



Inside Wheel Fenders Standard

#### **Specifications**

<u>opoonio</u>								
G4V 520	) & G4V 570	G6\	G6V 740		V PRO	G8V PRO		
<ul> <li>3pt Hi</li> <li>Overru</li> <li>High F 16x65</li> </ul>	,	$\diamond$ $\diamond$ $\diamond$	24' Working Width Overrunning Ratchet Clutch PTO 4 High Floatation Balloon Tires - 16x650/8 on Outside Rotors 2 Tandem Axles on Central Ro- tors	<ul> <li></li> <li><!--</th--><th>24' Working width 6 High Floatation Balloon Tires – 16x650/8 2 High Speed transport tires – 18x850/8 Hydraulic Tilt &amp; Lift Standard</th><th><ul> <li>◇</li> <li>◇</li> <li>◇</li> <li>◇</li> </ul></th><th>32' working width 8 High Floatation Balloon Tires – 16x650/8 2 High Speed transport tires – 350/50 R16 Hydraulic Tilt &amp; Lift Standard</th></li></ul>	24' Working width 6 High Floatation Balloon Tires – 16x650/8 2 High Speed transport tires – 18x850/8 Hydraulic Tilt & Lift Standard	<ul> <li>◇</li> <li>◇</li> <li>◇</li> <li>◇</li> </ul>	32' working width 8 High Floatation Balloon Tires – 16x650/8 2 High Speed transport tires – 350/50 R16 Hydraulic Tilt & Lift Standard	
570 ♦ U-Join	Speed transport tires on G4V nt Engagement On Wing Rotors y Built, Rectangular Tube-Frame	♦	U-Joint Engagement On Wing Rotors Heavy Built, Rectangular-Tube Frame	<ul><li></li><li></li></ul>	U-Joint Engagement On Wing Rotors Heavy Built, Rectangular-Tube Frame	<ul><li></li><li></li></ul>	U-Joint Engagement On Wing Rotors Heavy Built, Rectangular-Tube Frame	
<ul><li>♦ Standa</li><li>♦ Standa</li></ul>	el Fenders On Inside Tires dard Hydraulic Lift dard Hydraulic Tilt On G4V 570 el (manual crank tilt on 17')	$\diamond$	Wheel Fenders On Inside Tires Hydraulic Tilt & Lift Standard	$\diamond$	Wheel Fenders On Inside Tires Mechanical adjustment of the working angle Overrunning Ratchet Clutch PTO	$\diamond$	Wheel Fenders On Inside Tires Mechanical adjustment of the working angle Overrunning Ratchet Clutch PTO	









## **G6V 740PTH**

## **G6V 740PRO**

Model	Working Width	Lift Standard	Tilt	Rotors	Min HP	Tine Arms	Tires	Weight (Ibs.)	List Price			
G4V 520 3PH	17'	Hydraulic	Mechanical (Hyd. Option)	4	50	24	(4) 16x650/8	1,322	\$10,750			
G4V 520PTH	17'	Hydraulic	Mechanical (Hyd. Option)	4	50	24	(4) 16x650/8	1,080	\$9,690			
G4V 570PTH	19'	Hydraulic	Hydraulic	4	50	24	(2) 16x650/8 (2) 18x850/8	1,157	\$11,050			
G6V 740PTH	24'	Hydraulic	Hydraulic	6	50	36	(4) 16x650/8 (4) 18x850/8	2,160	\$15,120			
G6V 740PR0	24'	Hydraulic	Hydraulic	6	50	36	(4) 16x650/8 (4) 18x850/8	3,938	\$27,995			
G8V 980PR0	32'	Hydraulic	Hydraulic	8	50	48	(8) 16x650/8 (2) 350/50 R16	4,190	\$33,760			
OPTIONAL EQUIPM	OPTIONAL EQUIPMENT											
R0180-34069	Hydraulic Tilt O	ption for G4V 52	OPTH						\$970			

## Hay Tedder



The Tar River Tedder is built heavy in all the right places, this machine is designed to withstand the rigors of highvolume hay production.

The PRZ-3100 is a 10' tedder with 4"x8" tubing. This unit is a pull-type with a manual tilt and flat-bar tine arms.

On the 18' PRZ-5500, large 18" tires give the tedder great floatation across uneven terrain. Adjustable angling allow boundary tedding. Thick-walled tubular tine arms hold up long after the flat bar style ones would have bent. Hydraulic tilt and fold come standard.



Thick-Walled Tubular Tine Arms



Adjustable Angle and Tilt



Hyd. Tilt and Fold





Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.





#### Specifications:

#### PRZ-3100

- ♦ 10' Working Widths
- ◊ Overrunning Ratchet Clutch PTO
- ♦ High Flotation Tires
- ◊ Heavy Built, Rectangular Tube-Frame
- ♦ Packaged 2 per crate
- ◊ Manual Tilt

#### PRZ-5500 (includes all features of PRZ-3100 plus)

- ♦ 18' Working Width
- ◊ Wheel Fenders on Inside Tires
- ♦ Road Transport tires
- ♦ Hydraulic Lift
- ♦ Can be angled for "close to" fence tedding
- ♦ Hydraulic Tilt
- Heavy-walled tubular arms
- ◊ Integrated Locking collars and hex shaft drive units
- Ouble plated rotor supports
- ♦ Adjustable Wheel Yokes—Swivel and Tilt
- ◊ One Hydraulic Remote needed
- Overrunning Ratchet Clutch PTO

Model	Working Width	Lift	Tilt	Rotor Style	Rotors/ Arms	Min HP	Tires	Weight (Ibs.)	List Price	
PRZ-3100	10'	N/A	Mech.	N/A	2/12	15	(2) 15x600/6	507	\$3,830	
PRZ-5500	18'1"	Hyd.	Hyd.	U-Joint	4 / 24	35	(4)18x8.5/8	1,594	\$11,350	
10' tedders are	10' tedders are packaged 2 per crate (additional cost if purchased individually)									

## Hay Tedder

#### A New Addition to a Proven Lineup

The **PRZ-7900** 6-basket tedder is the newest addition to Tar River's reliable PRZ Series—joining the compact **PRZ-3100** (2-basket) and the versatile **PRZ-5500** (4-basket) models. Designed for larger operations, the PRZ-7900 delivers increased coverage, rugged performance, and easy transport, making it an excellent choice for high-output hay production.

The PRZ-7900 rounds out Tar River's PRZ Series with a larger, more capable option for farms ready to scale up. Whether you're stepping up from the PRZ-5500 or starting fresh with high-acreage demands, this tedder delivers the performance and reliability you expect from the Tar River name.

Hydraulically controlled angled tedding is standard.













Model	Working Width	Tilt	Rotor Style	Rotors/ Arms	Min HP	Tires	Weight (Ibs.)	Transport.	List Price
PRZ-7900	25'8"	Hyd	U-Joint	6/36	80	<ul> <li>(4) 18x850/8</li> <li>(2) 16 x 650/8</li> <li>(2) 10x75/15.3</li> </ul>	3,237	157" x 118"	\$22,950

## **Rotary Rake**

## SINGLE AND DOUBLE ROTOR CONFIGURATIONS



Enorossi's Single & Double Rotary Rakes come standard with pneumatic pivoting wheels and heavy, tubular tine arms that are removable for transport. The RR-350 has 11 rotor arms that sweep cleanly all hay types in any condition.

The ENODUO 780 is a center delivery double rotary rake with an adjustable working width from 23' to 25'6". It comes with four wheels per rotor for excellent stability on uneven ground and is semi-mounted with rear steering wheels for maximum maneuverability. The gentle raking action ensures high nutrient levels remain on the crop and in the bale - not in the field.



Tandem Wheel Axles



Heavy Duty, Sealed Oil Bath G-box



**Transport Position** 



## Specifications:

- Extra heavy duty frame and components
- ◊ Hydraulic transport lift standard
- ◊ Heavy-duty, sealed oil bath gearbox
- ♦ Large, high floatation tire
- ♦ Standard tandem axle
- Removable tine arms
- Great economic option for those smaller-range tractors and hilly conditions
- 20" Ground Clearance Hydraulic Lift for transport









Model	Working Width	Lift	Windrow	Min HP	Tine Arms	Tines	Weight (lbs.)	Ship Weight (Ibs.)	List Price
RR350	11'6"	3 Pt	Side	30	9	27	827	867	\$7,340
RR420 EVO PT	13' 9"	Pull-type Hydraulic	Side	30	11	44	1,370	1,470	\$11,480
ENODUO 780	23' - 25'6"	Semi-Mount Hydraulic	Center	70	22	88	3,950	4,400	\$36,715
TRACER 7802	25'6"	Semi-Mount Hydraulic	Side	70	22	88	4,080	4,400	\$39,750

## Rotary Rake

Tar River Implement's Single Rotary Rake comes standard with hydraulic height adjustment and heavy tubular tine arms that are foldable for transport. The ZRG-420 has 11 rotor arms that cleanly sweep all hay types in any condition. Wide angle constant velocity PTO shaft come standard. Replaceable wheel hubs ensure transportation is not a problem. The gentle raking action ensures high nutrient leaves remain on the crop in the bale, not in the field.

The ZRG-360 is a 3-point version with a 9 arm gearbox for use in tighter areas where a pull-type will not allow you to reach all areas of the field.



22

Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.

11 (6 folding)

1,489

Hyd.

Pull Type

# **Tedder Rake**



Enorossi's DR420 – 2 Rotor Tedder Rake is ideal for medium-sized and large farms requiring a multifunctional machine. It's the ideal solution for farmers who want to obtain both central and lateral windrows depending on the quantity of the harvested material. It can perform many different tedding and raking functions always with optimal processing of your highquality forage. Standard equipped with cardan shaft, protections, inverter and twin wheels. The high working speed of almost 10 mph allows outstanding performances.



Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.

24+18

1104

## **R-Rake**



The RR-248 was designed with the needs of the small hay farmer in mind. Ted and Rake with a single machine.

With a 48" working width, this rotary rake is capable of delivering an excellent quality of performance while still being compact enough to be used with a 20 HP tractor.

The high-quality but affordable materials make this rake durable and a great choice for budget farms.

With the RR-248's combination of performance, durability, and affordability, it is the next-best-thing for





Model	Working Width	Tine Arms	Tines	Weight (lbs.)	List Price
RR-248	48"	6	12	364	\$3,125





Two machines in one - rake and ted with the Tar River Implements Belt Rake! With its compact design and versatile functionality, the Belt Rake is an ideal hay tool for the small to medium sized hay producer. Great durability and low maintenance as well as simplicity of use are just a few benefits for this tedder-rake combination Belt Rake.

The D150-3 is a low profile design that can operate with any HP tractor. Simple and easy to use with very low maintenance. The 3 times per row make clean a sweep of your pasture.

Fast adjustments allow one to go from tedding to raking in a breeze.

D180-4 comes standard with 4 double tines per row and all the features of the D150-3. This extra set of tines is helpful in heavier hay crop conditions.



## **Specifications:**

- Heavy square tubing construction
- ◊ Heavy duty belts for long life
- A Rear Height adjustment wheels
- ♦ Front Pivot wheel

Model	Working Width	# of Belts	Tines x Crossbeam	Weight (Ibs.)	List Price
D150-3	71"	2	3	408	\$3,990
D180-4	83"	2	4	485	\$4,455

# 3 POINT WHEEL RAKE





An easy and efficient hay rake suitable for any type of forage. The spring system of the tool holder allows raking wheels to adapt to any type of ground with the correct pressure and without affecting the forage quality. Independent and interchangeable raking wheels mount on tapered roller bearings. Teeth made of flexible steel.



## **Specifications:**

- Heavy tubular frame with strategically placed bracing
- Molded steel hubs with tapered roller bearings
- ◊ 7 mm heavy spring steel teeth
- High quality powder-coat paint

RP3C has a specifically designed A-frame for smaller subcompact tractors.

Perfect tool for windrow turning or raking pine straw.

Model	# Wheels	Teeth per Wheel	Wheel Dia.	Work Width	Weight (lbs.)	List Price
RP3C	3	40	55"	6'5" - 7'11"	199	\$1,195
RP4	4	40	55"	8'6" - 9'6"	393	\$1,790
RP5	5	40	55"	11' 2" - 12'2"	464	\$2,075
akes are 2 per		\$100 net				

## CARTED WHEEL RAKE



The Enorossi Carted Wheel Rake, with its 15" tires and heavy 6.9 mm teeth, gives you the ability to cruise at high ground speeds with less worries about teeth breakage. Tapered roller bearings keep the wheels running smoothly and easily with minimum maintenance. Frame construction is thick-walled square tubing to give years of reliable service.

#### **Specifications:**

- Heavy square tubing construction on Rake Cart
- ◊ 205/70-15 tires standard
- $\diamond$   $\ \ \,$  Heavy tubular frame with strategically placed bracing
- Molded steel hubs with tapered roller bearings
- Optional Kicker wheel available

- ◊ 6.9 mm heavy spring steel teeth
- Ouble-action hydraulic cylinder
  - ◊ Compact design
  - A High quality powder-coat paint

Model	# of Wheels	Teeth per Wheel	Wheel Dia.	Work Width	Transport Width	Weight (Ibs.)	Ship Weight (Ibs.)	List Price
CADDY 8	8	40	55"	17'7'	8' 2"	1,324	1,409	\$7,060
CADDY 10	10	40	55"	21'	8' 2"	1,470	1,555	\$7,780
CADDY 12	12	40	55"	24' 3"	8' 2"	1,624	1,709	\$8,175
OPTIONAL EQ	UIPMENT							
R0180-31742 Kicker wheel attachment								\$950
R0180-31090	Select-a-valv	e (to raise one	e side only)					\$145

## BAT RAKE O DIAMOND DISCOUNT

## HIGH CLEARANCE CARTED RAKE



Enorossi's Bat Rake is the new standard for Hay Rake Caddies. Available in 8, 10 and 12 wheel sizes, the Bat Rake comes in a Single Wheel configuration allowing each individual raking wheel to follow all types of ground contours. Equipped with 60" diameter raking wheels and 7.5 mm tines, the Bat Rake's raking wheels are arguably the best raking wheel on the market today. The heavy spring tines, provide for excellent wear and strong resistance to breakage. The heavy-built frame and high profile of the Bat Rake give a full 32" of ground clearance allowing it to rake in all types of ground contours in heavy hay conditions.

### **Specifications:**

- Independent rake wheel arms to follow all ground contours
- ♦ High Clearance 32" of Ground Clearance
- Perfect for heavy hay
- Easy windrow width adjustment
- Heavy built and low maintenance
- $\diamond$  60" raking wheels with 7.5 mm tines

- ◊ Heavy built and low maintenance
- ♦ 205/70-15 tires standard
- ◊ Heavy tubular frame with strategically placed bracing
- Molded steel hubs with tapered roller bearings
- Ouble-action hydraulic cylinder
- Ocompact design

Model	# Wheels	Teeth per Wheel	Wheel Dia.	Max Work Width	Teeth Diameter	Weight (Ibs.)	Ship Weight (Ibs.)	List Price	
BAT 8-H	8	40	60"	18'5"	7.5 mm	1,445	1,595	\$9,475	
BAT 10-H	10	40	60"	21'8"	7.5 mm	1,644	1,794	\$10,275	
BAT 12-H	12	40	60"	24'3"	7.5 mm	1,886	2,036	\$11,285	
OPTIONAL EQ	UIPMENT								
R0180-32136	R0180-32136 Kicker wheel attachment								
R0180-32659	Wind Guard	for Rake Whee	els (Sold Ind	ividually)				\$54	

# **POWER RAKE**

In partnership with Enorossi, Tar River Implements introduces the Power Rake.

This new high-clearance rake is available in 8, 10, and 12 wheel sizes.

Equipped with 60" diameter raking wheels and 7.5 mm tines, the Power Rake's raking wheels are the best raking wheel on the market today. The heavy spring tines,

provide for excellent wear and strong resistance to breakage. The heavy-built frame and high profile of the Power Rake give a full 32" of ground clearance allowing it to rake in all types of ground contours in heavy hay conditions.

# Image: constraint of the set of the

## Shown w/ Optional Wind Guards & Kicker Wheels

## Specifications:

- Independent rake wheel arms to follow all ground contours
- ♦ High Clearance 32" of Ground Clearance
- Output Perfect for heavy hay
- $\diamond\quad \text{Easy windrow width adjustment}$
- ◊ Heavy built and low maintenance
- $\diamond$  ~~ 60" raking wheels with 7.5 mm tines

- $\diamond$   $\hfill Heavy built and low maintenance$
- ◊ 205/70-15 tires standard
- $\diamond$   $\ \ \,$  Heavy tubular frame with strategically placed bracing
- $\diamond$   $\quad$  Molded steel hubs with tapered roller bearings
- Ouble-action hydraulic cylinder
- Compact design

Model	# Wheels	Teeth per Wheel	Wheel Dia.	Max Work Width	Teeth Diameter	Weight (Ibs.)	Ship Weight (Ibs.)	List Price					
PR 8	8	40	60"	18' 11"	7.5 mm	1,766	1,916	\$10,750					
PR 10	10	40	60"	21' 8"	7.5 mm	1,987	2,137	\$11,125					
PR 12	12	40	60"	24' 3"	7.5 mm	2,318	2,466	\$11,475					
OPTIONAL EQU	OPTIONAL EQUIPMENT												
R0180-38089	Power Rake	Kicker wheel	attachment					\$1,950					

# MAXIMUS RAKE





The MAXIMUS Rake has been designed to match the customer's high demands. It is available in 3 sizes; 12, 14, and 16 wheel configurations. All versions feature independent rake wheel arms using a unique double rod spring system to maintain constant pressure of the raking wheels to the ground. The heavy duty frame and wide tire spacing give great stability in heavy conditions.

#### **Specifications:**

- Independent Rake Wheel Arms to Follow All Ground Contours
- Perfect for Heavy Hay
- Easy Windrow Width Adjustment
- 60" Raking Wheels with 7.5 mm Tines

- Heavy Duty and Low Maintenance
- ◊ Tandem Tires Standard
- Heavy Tubular Frame with Strategically Placed Bracing
- Molded Steel Hubs with Tapered Roller Bearings
- Optional 2 front/1 rear Kicker Wheel available

Model	# of Wheels	Teeth per Wheel	Wheel Dia.	Max Work Width	Teeth Diameter	Weight (Ibs.)	List Price
M12	12	40	60"	24'	7.5 mm	3,064	\$19,775
M14	14	40	60"	27'	7.5 mm	3,306	\$20,150
M16	16	40	60"	30'	7.5 mm	3,748	\$23,125
OPTIONAL EQUIPM	ENT						

MAX-001	Kicker wheel attachment	\$2,100
R0180-32659	Wind Guard for Rake Wheels (Sold Individually)	\$54
R0180-36284	M14 to M16 wheel conversion kit	\$3,335

## HIGH CAPACITY EASY RAKE





The Enorossi High Capacity Easy Rake is both easy to assemble and easy to use. Assembly time is typically 1/2 that of other High Capacity Rakes.

The Easy Rake has been designed with a series of innovations that are unique to the market that improves operator productivity. The two sides are independent from one another allowing the machine to operate with a single side. Simple swath adjustment is obtained by a system of easy-to-use bushings.



#### **Specifications:**

- $\diamond \quad \text{Heavy square tubing construction} \\$
- $\diamond \qquad 205/70\text{-}15 \text{ tires standard}$
- ♦ 4 3/4 Heavy tubular frame with strategically placed bracing
- ♦ Molded steel hubs with tapered roller bearings
- ♦ 7.5 mm diameter heavy spring steel teeth

- Occupact design
- High quality powder-coat paint
- 40 teeth per wheel
- 60" Wheel diameter
- Optional Double Kicker wheel available

10 12	21' 5"	4	2,870	¢40,400
10			_,	\$18,420
12	24' 4"	4	3,046	\$19,350
14	27' 4"	6	3,709	\$22,810
16	31' 4"	8	5,180	\$33,660
18	34' 3"	12	6,945	\$43,280
20	37' 5"	12	7,385	\$44,790
22	39' 8"	12	8,050	\$51,680
-	16 18 20	16         31' 4"           18         34' 3"           20         37' 5"	16         31' 4"         8           18         34' 3"         12           20         37' 5"         12	16         31' 4"         8         5,180           18         34' 3"         12         6,945           20         37' 5"         12         7,385

## MINI ROUND BALER OF DESCRIPTION OF D



Perfect for the small farmer who wants to produce their own hay. It's low cost and a time saver. The affordable SRB-870 or SRB-870NW allows you to control when you bale, not others. The auto twine binding system alerts the operator, who simply pushes a button, to open the rear door hydraulically, thus dropping the bale.

The net wrapping system of the SRB-870NW works the same way except with even better weather resistance, and reduction of loss from heavy handling with net wrapping. The baler comes with a self-contained hydraulic pump. Only a connection to the tractors 12V battery is needed to operate the baler making it easy and mess free.

 $\Diamond$ 



### SRB-870 Twine Baler

- 3 pt. Category 1 Hitch
- ◊ 18-30 HP
- ♦ Electronic Control Box
- ◊ Includes 1 Roll of 8500' Twine

#### SRB-870NW Net Wrap Baler

- ◊ 3 pt. Category 1 Hitch
- ◊ 18-30 HP
- ◊ Electronic Control Box
- ◊ Includes a starter roll of net wrap (approx. 50 bales)

Model	Bales	Pickup	Tractor HP Min	Working Capacity	Weight (lbs.)	List Price				
SRB-870	23" x 28"	2' 6"	18 HP	80-100 bales/hour	1,025	\$7,850				
SRB-870NW	23" x 28"	2' 6"	18 HP	80-100 bales/hour	1,102	\$7,950				
REPLACEMENT TV	REPLACEMENT TWINE/WRAP									

## TG0800Replacement 8500' Twine\$37 (Parts Discount)SRBW006Replacement 26" x 5000' Net Wrap Roll\$125 (Parts Discount)

32

## STATIONARY BALE WRAPPER I CONO-WIG





Bale Guides To Provide **Even Placement of Film** Wrap



Film Slicer At The End of Rotary Table Cuts Film After Bale Is Unloaded and New One Is Set Back **On For Continuing Operation** 





Quality Components Such As The Hydraulic Motor & Bevel Gears Ensure Long Machine Life

Too much rain? Try wrapping your hay with the Econo-Wrap Single Bale Wrapper. The Econo-Wrap Bale Wrapper was designed with the average farmer in mind and is ideal for smallscale hay producers. This 3 Pt. Hitch Stationary model will wrap bales up to 4' x 5' round bales.

## **Specifications:**

- Wraps round bales up to 4'x5' (weighing  $\diamond$ up to 2,100 lbs.)
- Hooks up to 3 pt. Hitch and runs off of  $\Diamond$ the auxiliary hydraulics
- When done wrapping, lift 3 pt. hitch to  $\Diamond$ unload bale
- $\diamond$ Unit is equipped with bale counter
- Approx. wrap time: 90 seconds  $\Diamond$



Model	Transport	Film Size	Max. Bale Size	Max. Bale Weight	Min. HP	Weight (Ibs.)	List Price	
EW-450	3 Pt. Hitch	20" or 30"	4' x 5'	2,100 lbs.	40 HP	1,091	\$5,795	
OPTIONAL EQUIPMENT								
EW-001A	Vertical Bale Positioner EW-450						\$605	

## **SELF-LOADING**



Upgrade your baling operation with the Econo-Wrap EW-1800TA, a streamlined wrapper designed for solo operators. With the ability to wrap bales up to 4' x 5', this fully automated machine requires only one button push to initiate the wrapping process.

Effortlessly fit the bale into the lifting arm cradle, press the button and watch as the EW-1800TA takes overlifting the bale onto its turntable and beginning the automatic wrapping process. Enjoy the freedom to drive up to the next bale while the machine continues wrapping, dumping it only when fully finished. The Econo-Wrap EW-1800TA is the perfect partner for your baling needs.



Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.

# BALE WRAPPER STRUCTURE



### **Specifications:**

- Wraps round bales up to 4'x5' (weighing up to 2,425 lbs.)
- Fully automated electronic control allows user to select from 3 cycles (Automatic, Semi-Automatic or Manual)
- ◊ Side tip damper standard
- Unit is equipped with bale counter
- ◊ 3 film roll holders



Model	Transport	Film Size	Max. Bale Size	Max. Bale Weight	Min. HP	Weight (lbs.)	List Price
EW-1800TA	Trailer-Type	20" or 30"	4' x 5'	2,425lbs.	45 HP	4,520	\$28,395

# **SELF-LOADING BALE WRAPPER**



Enorossi's BW 100 EVO is a mounted satellite bale wrapper with self-loading device that allows you to perform different operations on the move. It is hydraulically operated with one remote and standard with brake and vertical bale unloading kit.



Model	Transport	Film Size	Max. Bale Size	Max. Bale Weight	Min. HP	Weight (lbs.)	List Price
BW 100 EV0	3 pt. Hitch Cat. 2	20" or 30"	4' x 5'	2,200 lbs.	80 HP	1,880	\$21,450
### INLINE BALE WRAPPER EKEMCO



Eliminate the rush of baling hay for threat of an oncoming storm. Reduce the amount of waste at feeding time, improve your hay harvest efficiency and reduce loss in harvest and storage. Accomplish all of this with the KEMCO Inline Bale Wrapper, the fastest wrapper on the market, which wraps up to 4 bales per minute. As fast as you put them up, they will be wrapped!







Model	# of Plastic Dispensers		Wrapping Width	Remote Steering	Engine	Self- Propel Drive	Film Sensor	Hyd. Tailgate Lift	LED Lights	Weight (Ibs.)	List Price
KEMCO 355 PRO 2	3	Round / Square	6'6" Round / 5'6" Square	Yes	20 HP	Dual Wheel	Std	Std	2	6,320	Call for Pricing

# **SIDE SHIFT ROTARY TILLER**



Specifically designed and engineered for sub-compact tractors in the 15-25 Horsepower range, the Tar River DLT Series Rotary Tiller is built with 4 blades per flange and a sturdy #80 chain drive system to give you years of reliable service. The Slip-Clutch PTO protection comes standard.

Available in 42" and 50" working widths, the Tar River DLT Series Rotary Tiller is perfect for all your small-tractor tilling needs.



Model	Working Width	Blades per flange	Drive	HP	Weight (Ibs.)	Ship Weight (Ibs.)	List Price				
SUB-COMPACT SERIES											
DLT-S42	42"	4	#80 Chain	15 - 25	304	375	\$1,750				
DLT-S50	50"	4	#80 Chain	15 - 25	348	429	\$2,160				

# COMPACT ROTARY TILLER

Built to fit the needs of the compact tractor market, the Tar River TXG Series Rotary Tiller will work great at tilling up your small garden plots. It comes standard with a "gear-to-gear" drive system, 6 blades per flange and Slip-Clutch PTO protection.

Available in 41", 48" and 59" working widths, the Tar River TXG Series Rotary Tiller is perfect for all your small-tractor tilling needs.



Model	Working Width	Blades per flange	Drive	HP	Weight (Ibs.)	Ship Weight (Ibs.)	List Price
COMPACT SE	RIES						
TXG-040	41"	6	Gear	15-30	337	392	\$2,265
TXG-050	48"	6	Gear	15-30	374	434	\$2,325
TXG-060	59"	6	Gear	18-30	412	477	\$2,385

# MEDIUM DUTY ROTARY TILLER OF DIAMOND

Using quality components that are made to last, the YCT Series Rotary Tiller by Tar River Implements is built heavily enough to handle your tilling needs and for the price, it can cut through the competition.

Engineered for tractors from 30 to 60 Horsepower, the Tar River YCT Series Rotary Tiller comes with 6 blades per flange, slip clutch PTO protection and gear drive side transmission. It is available in 4', 5', 5.5', 6' and 7' models.

With its sleek and heavy design, paired with the quality components and its incredible price, the Tar River Rotary Tiller is ahead of its class.



Model	Working Width	Blades per flange	Drive	HP	Weight (Ibs.)	Ship Weight (Ibs.)	List Price
MEDIUM DUT	Y SERIES						
YCT-050	49"	6	Gear	30 - 50	525	554	\$2,815
YCT-060	58"	6	Gear	30 - 50	542	608	\$2,895
YCT-066	66"	6	Gear	35 - 50	596	669	\$3,185
YCT-074	72"	6	Gear	40 - 50	640	718	\$3,325
YCT-082	81"	6	Gear	45 - 60	702	757	\$3,765

## REVERSE ROTATION ND ROTARY TILLER

Tar River Implements is proud to provide the YCT-R Series Reverse Rotation Rotary Tiller. Reverse Rotation tillers provide a cleaner and smoother finish in less passes than a forward rotation tiller. These tillers will cut the overlying growth and bury them under the surface.

Engineered for tractors from 30 to 60 Horsepower, the Tar River YCT-R Series Rotary Tiller comes with 6 blades per flange, slip clutch PTO protection and gear drive side transmission. It is available in 5' and 6' working widths.



### **YCT-R Series**





### Specifications:

- ◊ Gear Drive Transmission
- ♦ 6 Blades Per Flange
- ♦ PTO with Slip Clutch
- Over Coat Paint
- ◊ Solid A Frame
- ♦ Large Diameter Rotor
- ◊ Labyrinth Rotor Bearing Shielding
- ◊ Front Dirt Shield
- ◊ 7" Tilling Depth

Model	Working Width	Blades per flange	Drive	HP	Weight (Ibs.)	Ship Weight (Ibs.)	List Price				
REVERSE TINE MEDIUM DUTY SERIES											
YCT-R60	58"	6	Gear	30 - 50	557	623	\$3,145				
YCT-R74	72"	6	Gear	40 - 50	654	734	\$3,625				

# HEAVY DUTY ROTARY TILLER

Built to suit the needs of larger tractors and more agricultural applications, the Tar River RXT Series Rotary Tiller is rated for up to 120 HP tractors. Using spiral center gearbox gears, extra thick rotor assembly and a tough A-frame, the RXT tiller can handle your roughest jobs.

Available in working widths of 66", 73", 84 and 92".



### **Specifications:**

- ◊ Gear Drive Transmission
- 6 Blades Per Flange
- ◊ PTO with Slip Clutch
- Over Coat Paint

- ♦ Large Diameter Rotor
- ◊ Solid A Frame
- ♦ Waterproof Rotor Supports
- 8" Tilling Depth

Model	Working Width	Blades per flange	Drive	HP	PTO Driveline	Weight (Ibs.)	Ship Weight (Ibs.)	List Price			
HEAVY DUTY SERIES											
RXT-072	66"	6	Gear	50-120	Series 6 S/C	945	1,053	\$5,170			
RXT-080	73"	6	Gear	55-120	Series 6 S/C	970	1,075	\$5,695			
RXT-088	85"	6	Gear	60-120	Series 6 S/C	1,015	1,121	\$5,995			
RXT-096	92"	6	Gear	65-120	Series 6 S/C	1,069	1,183	\$6,375			

42

# HD MULTI-SPEED GEARBOX ROTARY TILLER

Built heavy for agricultural applications, the Tar River CXT Series Rotary Tiller is rated for tractors up to 130 HP and available in working widths of 86", 95, 104", 112" and 121".

The CXT tillers are designed with multispeed gearboxes to handle your ever changing conditions. The multi-speed gearbox is designed for easy gear access to allow the rotor speed to be changed quickly as you move to different field conditions. A large thick walled rotor is sustained by water proof rotor supports for wet conditions. Decks are double layered to keep stone indentations to a minimum.



Model	Working Width	Blades per flange	Drive	HP	PTO Driveline	Weight (lbs.)	Ship Weight (Ibs.)	List Price
CXT-095	95"	6	Gear	70-130	Series 8 S/C	1,762	1,862	\$9,875
CXT-104	104"	6	Gear	75-130	Series 8 S/C	1,876	1,895	\$10,750
CXT-112	112"	6	Gear	80-130	Series 8 S/C	2,081	2,317	\$11,125
CXT-121	121"	6	Gear	85-130	Series 8 S/C	2,115	2,410	\$12,250

### Crop Seeder ( ) RAR RIVER

Tar River Implements offers an economical solution to your seeding needs.

The DRL-048 & DRL-072 come with double opening discs to plant grass, corn, beans, oats and more. The seeder comes equipped with two stainless steel boxes with closeable slides for each row. Apply fertilizer to each row while planting.

The DLR is designed to be used as a secondary tillage tool.

Ground conditions need to be worked up or tilled prior to use.





### **CONVENTIONAL DRILL**

### FOR USE IN PREPARED GROUND





### **Specifications:**

- ♦ 6" Spacing
- ◊ Spring Loaded Double Disc Opener
- O Disc Scrapers
- Oivided Stainless Steel Hopper
- ◊ Standard Seed/Fertilizer seed cups on front and rear
- ♦ Full width Cage Roller
- Output Compaction scrapers
- ◊ Rear Roller
- DRL-048 Hopper Capacity: 3.50 Cu. Ft. Front Hopper
   2.50 Cu. Ft. Rear Hopper
   DRL-072 Hopper Capacity: 5.00 Cu. Ft. Front Hopper
   4.00 Cu. Ft. Rear Hopper



Model	Working Width	Working Depth	Min HP Req	Front Cup/ Rear Cups	Spacing	Double Disc openers	Cat. Hitch	Weight (Ibs.)	List Price
DRL-048	48"	3/4" - 2"	15	7+7	7"	7 Sets	1	585	\$4,125
DRL-072	68"	3/4" - 2"	20	10 + 10	7"	10 Sets	1&2	741	\$4,825

# NO-TILL DRILL

The SAYA-505 (55") & SAYA-507 (78") got a facelift! They are still cost effective Light Duty No-Till Drills with front coulter package, but with new and improved features.

Q പ്ick Hitch <sup>Compatible</sup>

The 505 has 7 and the 507 has 10 swept back spring loaded double disc openers making seeding easy and economical. The Large seed and Legume cups allow for precise seeding in a no

- till operation. **Stainless steel hoppers** prevent rust and keep your drill in fine working shape for years to come. The <u>NEW</u> SAYA-907 has a 75" working width and comes with a 3 compartment seedbox which contain 3 different seedcups for seeding of any type of seed.

The front section comes with a dual section seedcup that splits between large seeds (corn and soybean sizes) to grass seeds such as wheat and rye. The middle section has a flow adjustable gearbox with special gear seedcups designed for the fluffy warm season Native grasses. There is no need to change chains and sprockets to adjust the flow. A simple handle on the gearbox smoothly increases or decreases seed output. Both the front and middle seedcups feed into a heavy cast iron double disc opener.

The rear box contains high precision metering seedcups for the tiny legume seeds. Seeds dispersed from these cups are spread out behind the machine in order to prevent them from becoming buried too deep.







Warm Season Native Grass Box available on SAYA-907 ONLY. Perfect for metering Virginia Wildrye, Yellow Indiangrass, or a variety of other native grasses



**Cast Iron Roller Option** 

### SAYA—Light Duty No-Till Drill For use in Light No–Till Applications

### Specifications:

- ♦ 7.5" Spacing
- $\diamond \quad \text{Spring-Loaded Coulter discs}$
- Spring-Loaded Double Disc
   Opener with Cast Iron Hubs
- Cast Iron Swept-back Disc carriers
- O Disc Scrapers
- Oivided Stainless Steel Hopper
- Standard Seed/Fertilizer seed cups on front

- Legume Seed cups on rear
- ♦ Full width Cage Roller
- Occupaction scrapers
- SAYA-505/507 Front Hopper Capacity: 4.00/5.5 Cu. Ft.
- ◊ SAYA-505/507 Rear Hopper Capacity: 3.00/4.5 Cu. Ft.
- SAYA-907 Front Hopper/ Native Grass Box Capacity: 4.5 Cu. Ft.
- ◊ SAYA-907 Rear Hopper Capacity: 3.8 Cu. Ft.









Model	Working Width	Working Depth	Min HP Req	Front Cup/ Rear Cups	Spacing	Double Disc openers	Cat. Hitch	Weight (Ibs.)	List Price		
SAYA-505	55"	3/4" - 2"	30	7	7.5"	7 Sets	1&2	1,036	\$6,895		
SAYA-507	75"	3/4" - 2"	35	10	7.5"	10 Sets	1&2	1,400	\$8,740		
SAYA-907	75"	3/4" - 2"	35	10	7.5"	10 Sets	1&2	1,499	\$10,450		
OPTIONAL EC	UIPMENT										
SAYA-CR05	SAYA-505	SAYA-505 Cast Iron Roller - in addition to									
SAYA-CR07	SAYA-507	or SAYA-90	7 Cast Ir	ron Roller - iı	n addition	to			\$1,770		

## **NO-TILL DRILL Press Wheels**

Introducing the SAYA No Till seeder with Press wheel configuration. All the same great features as the SAYA models with cage roller basket, but now available with press wheels.



MPLEMEN

Qtlick

Hitch

Compatible



Model	Working Width	Working Depth		Front Cup/ Rear Cups		Double Disc openers	Cat. Hitch	Weight (Ibs.)	List Price
SAYA-505PW	55"	3/4" - 2"	30	7	7.5"	7 Sets	1&2	1,142	\$8,275
SAYA-507PW	75"	3/4" - 2"	35	10	7.5"	10 Sets	1&2	1,532	\$10,495
SAYA-907PW	75"	3/4" - 2"	35	10	7.5"	10 Sets	1&2	1631	\$12,540

### Pull Type NO-TILL DRILL

Perfect seeder for your Food Plots or seeding but with a Pull Type hitch for RTV's or smaller tractors. Comes with Electrical actuator for simple transfer from working to transport position. The SAYA-PT505 comes with 7 ground cutting coulters and double disc openers. Heavy spring loaded press wheel ensure excellent seed/ground contact for superb germination.

#### **Specifications:**

- ♦ 7.5" Spacing
- ♦ Spring-Loaded Coulter discs
- ♦ Spring-Loaded Double Disc Opener with Cast Iron Hubs
- ◊ Cast Iron Swept-back Disc carriers
- O Disc Scrapers
- Oivided Stainless Steel Hopper
- ◊ Standard Seed/Fertilizer seed cups on front
- ◊ Front Hopper Capacity: 4.00 Cu. Ft.
- Rear Hopper Capacity: 3.00 Cu. Ft.
- Std with Press Wheels





Model	Working Width	Working Depth	Min HP Req	Front Cup/ Rear Cups	Spacing	Double Disc openers	Weight (Ibs.)	List Price
SAYA-PT505	55"	3/4" - 2"	18	7	7.5"	7 Sets	1,532	\$8,795

# DISC HARROW WITH SEEDER ET TAR RIVER

The DHDS-63 is a durable disc harrow with seeder. It is equipped with 10 disc heads in the front and back, which efficiently cuts and pulverizes the soil, creating an ideal seedbed for optimal germination. With its adjustable disc heads and precise seed metering system, the DHDS-63 provides accurate and uniform seed distribution. The front box distributes the seed into the disced soil. This allows for a deeper planting depth. The rear seed box has the legume seed cups and the seeds are distributed behind the disced area and rolled in the ground by the rear roller.







Transport Position Unit Folds into Transport Position for easy and hassle free moving.



Model	Working Width	Working Depth	Min HP Req	Front Cup/ Rear Cups	Disc Heads	Cat. Hitch	Weight (Ibs.)	List Price
DHDS-63	63"	3" - 4"	25	7	10 (front & rear)	1	803	\$8,950

## **CORN/SOYBEAN PLANTER**

Tar River Seed Planter is an excellent choice for planting Corn, Soybean, Sorghum or Millet. Built to last with stainless steel seed and fertilizer hoppers the CSP-2R or CSP-4R are cost effective units for small farmers. Units come standard with Corn and Soybean plates, optional Sorghum and Millet plates are available. The SCP-4R 4-row units comes standard with hydraulically lifting row markers, which requires 1 remote. Rows are spaced at 36" during assembly but are adjustable.



Model	Description	HP	Hitch	Weight (lbs.) List Price			
CORN/SOYB	EAN PLANTER						
SCP-2R	2 Row Corn Planter	35	Cat 1	425	\$4,425		
SCP-4R	4 Row Corn Planter w/ Row Marker	Cat 1	925	\$8,995			
OPTIONAL EQ	)UIPMENT						
SCP-SGP	Sorghum Plate Assy			\$8	35		
SCP-MLP	Millet Plate Assy.			\$8	35		
SCP-RM	Row Markers (Hydraulic lift) *Comes stan	dard on SCP-4R*		\$995			

# GREENSCAPE E GREENSCAPE

### **750 SERIES**



High Precision Large Seedcup



Smaller Legume Seedcup



Greenscape 750 FOOD PLOTTER No-Till Drills are the latest in the Greenscape family of the most reliable seeders produced in the US over the past 20 years. High precision seed boxes and flow control make seeding a breeze with the ability to drill many different varieties and sizes of seed into all types of planting conditions.

Heavy built, but constructed to be able to be handled by tractors as low as 40 HP, The FOODPLOTTER line is designed for planting deer food plots around woodlands or high precision pasture seeding in the fall.

With 10 coulters at 7.5" spacing, high precision large seed seedcups accurately drop seeds into the openings. A separate Legume Seedbox with high precision seedcups accurately drop seed along a "splash pan" that rains the small seed over the soil. A packer roller system with Nylon rings or optional cast iron rollers help press the seed into the ground and close up the cuts made by the disc openers.

The NEW 750-4 has all the same great qualities of the 750-2 but with a Warm Season Native Grass Box. Perfect for metering Virginia Wildrye, Yellow Indiangrass, or a variety of other native grasses!

#### Specifications:

- Ohree Point Hitch Cat. 1&2
- Heavy tubular frame construction
- All ground driven, no PTO shaft or gearbox to maintain
- Precise seed metering cups with individual clean out gates
- Rear roller packer rings to firm and smooth seedbed
- Water tight seed box with agitator shaft calibration chart and seeding rate chart
- ◊ 10 Cast Iron double disc openers spaced at 7.5"
- ♦ Spring loaded coulters to cut through tough ground
- Optional Cast Iron roller rings

### **NO-TILL DRILL**



Model	Description	Weight (lbs.)	Ship Weight (Ibs.)	List Price					
750-2	75" No-Till Drill with Large Seed and Precision Legume Seedbox	1,771	1,942	\$13,600					
750-4	75" No-Till Drill with Large Seed, Precision Legume, and Warm Season Native Grass Seedbox	1,974	2,145	\$16,970					
OPTIONAL EQUIPMENT									
GSC-024	Cast Iron Rings (in lieu of nylon rings)			\$990					
GSC-025	Rear roller scraper - 750 Models Nylon			\$255					
GSC-026	Rear roller scraper - 750 Models Cast Iron			\$255					
GSC-750CR	Complete Set of Aftermarket Cast Iron Rings			\$1,765					

## GREENSCAPE E STATE GREENSCAPE

The Greenscape represents a totally new concept in seeding. Being neither a grain drill nor a PTO driven seeder, the Greenscape effectively prepares the soil, drops and lightly covers the seed, and then firmly presses the soil for a perfectly prepared seedbed. It is designed to achieve a perfect pattern across the working width of the machine; no row effect as with drills or knife type over seeders.

Ground driven – no PTO shafts or gearboxes to maintain, and requires only a 35 HP (50 HP on 84" model) tractor to operate. When equipped with the optional precision small seed box and Native Seed box the Greenscape will plant virtually any type or size seed at any rate.

This machine will seed into all conditions, including primary seeding into prepared ground or overseeding into existing vegetation. Available in 60" and 84" working widths.

#### **Specifications:**

- Three Point Hitch Cat. 1&2
- ◊ Heavy tubular frame construction
- All ground driven, no PTO shaft or gearbox to maintain
- Precise seed metering cups with individual clean out gates
- Rear roller packer rings to firm and smooth seedbed
- Water tight seed box with agitator shaft calibration chart and seeding rate chart
- Driven spiked rollers crumble soil just enough for perfect seed-to-soil contact
- Exclusive Torque Arm keeps constant adjustable down pressure on rear cultipacker
- Broadcast across full width of working area no row effect as with PTO driven, knife type machines or sod drills

#### Benefits:

- $\diamond$  High ground speed up to 7 MPH
- Full width broadcast coverage NO ROW EFFECT
- ♦ Seed or overseed in any condition
  - Fields
  - Groomed Turf
  - Prepared ground
- Abrasive-Resistant mining steel tines for extremely high wear
- Front Roller aggressively drives second roller 42% faster
- High quality High precision seed cups for precise seed distribution
- Seed disengagement system for aeration & Seedcup safety shear pin
- Reinforced Nylon or Cast Iron corrugated roller rings
- Quick Hitch compatible reinforced three-point (Cat 1 & 2)
- ◊ <u>Available Hoppers</u>
  - Standard Large-Seed Box
  - Precision Legume Seed box
    - Native Grass Seed Box
    - Stainless Steel Fertilizer box







Seeder with 3 Boxes

### **CONSERVATION SEEDER**





Qປໍick

Model	Description 60" Model	Weight (Ibs.)	Ship Weight (Ibs.)	List Price
600-1	60 Inch Base Unit with 1 large-grass Seed box	1,325	1,545	\$8,480
600-2	60 Inch Base Unit with 1 large-grass Seed box + 1 Precision Legume Seed box	1,380	1,600	\$9,975
600-3	60 Inch Base Unit with 1 large-grass Seed box + 1 Precision Legume Seed box + 1 Stainless Steel Fertilizer Hopper	1,490	1,710	\$13,405
600-4	60 Inch Base Unit with 1 large-grass Seed box + 1 Precision Legume Seed box + 1 Native Grass Seed box	1,557	1,710	\$12,905
600-5	60 Inch Base Unit with 2 large-grass Seed boxes + 1 Precision Legume Seed box	1,545	1,710	\$12,420
Model	Description 84" Model			
840-1	84 Inch Base Unit with 1 large-grass Seed box	1,960	2,210	\$13,060
840-2	84 Inch Base Unit with 1 large-grass Seed box + 1 Precision Legume Seed box	2,084	2,334	\$14,940
840-3	84 Inch Base Unit with 1 large-grass Seed box + 1 Precision Legume Seed box + 1 Stainless Steel Fertilizer Hopper	2,565	\$18,950	
840-4	84 Inch Base Unit with 1 large-grass Seed box + 1 Precision Legume Seed box + 1 Native Grass Seed box	2,409	2,659	\$18,660
840-5	84 Inch Base Unit with 2 large-grass Seed boxes + 1 Precision Legume Seed box	2,315	2,565	\$17,900
OPTIONAL E	EQUIPMENT:			
Model	Description		List Price	Э
GSC-001	Cast Iron Rings - 600 Model (in lieu of nylon rings)		\$760	
GSC-004	Cast Iron Rings - 840 Model (in lieu of nylon rings)		\$1,080	
GSC-003	Rear roller scraper - 600 Models Nylon		\$195	
GSC-005	Rear roller scraper - 840 Models Nylon		\$255	
GSC-007	Rear roller scraper - 600 Models Cast Iron		\$195	
GSC-006	Rear roller scraper - 840 Models Cast Iron		\$255	
GSC-600R	Complete Set of Aftermarket Cast Iron Rings (600 Model)		\$1,415	
GSC-840CR	Complete Set of Aftermarket Cast Iron Rings (840 Model)		\$1,920	





Qulick

The Tar River Implement Roller Crimper is a tool designed to terminate cover crops by crimping the stalk rather than cutting it during its "dough stage". This process has several benefits, including the conservation of soil moisture, reduction of erosion, lessens the need for herbicides and addition of organic matter to the soil. It also suppresses weed growth and helps to cool soil temperatures during the summer months.

It is available in an 6', 8' and 10' working widths and is a useful tool for farmers and agricultural professionals who want to manage their soil health.



Model	Working Width	Overall Width	Min. HP	Cat. Hitch	Weight (lbs.)	Max Weight w/ Water	List Price
CMP-6	72"	77"	30	CAT 1-2	1,127	1,564 lbs.	\$5,775
CMP-8	96"	102"	40	CAT 1-2	1,404	1,987 lbs.	\$6,525
CMP-10	120"	124"	50	CAT 1-2	1,740	2,480 lbs.	\$7,995

# **BALE UNROLLER**



The Tar River Implement Bale Unroller is proudly made in the USA. It is designed to mount easily on your tractor's 3-point hitch, grips the bale at both ends and rotates on a central axis, using ground friction to unroll hay like a carpet—no additional tools needed. Ideal for feeding large round bales, it reduces waste by unrolling only what cattle will eat in an hour. Feed from the tractor seat while minimizing manure buildup and naturally spreading seeds across your pasture.



Model	Bale Size	Hydraulic Opening	Weight (lbs.)	List Price
TRBU-100	4' & 5'	Standard	310	\$2,465

# **CARTED CHAIN HARROWS**





Dethatch dead growth and rejuvenate grass and pasture fields with the Tar River Carted Harrow. Available in 20' and 24' working widths, the heavy 5/8" harrow tines keep your pasture healthy and vibrant.

The sturdy design of the Tar River Carted Harrow which easily folds into transport position makes it the obvious choice for your pasture renovation needs.



20' Carted Harrow

24' Carted Harrow



Model	Description	Center Sections	Wing Sections	Wing Fold	List Price
CH-20	20' Carted Harrow	2 each 4' x 6' x 5/8" chain	1 each 6' x 6' x 5/8" chain	Hydraulic	N/A
CH-24	24' Carted Harrow	2 each 4' x 6' x 5/8" chain	2 each 4' x 6' x 5/8" chain	Hydraulic	\$12,750

### CAST IRON HARROW



ickلi Qںlick

Compatible

Take care of your barnyards, pasture fields and horse arenas with four sizes of the Tar River Cast Iron Harrow.

Cat. 1, 3 point hitch compact design make it easy to hook up and store. The reversible cast iron tines and the heavy tubular design will give you years of use.



### **Specifications**

- ♦ Heavy Duty pipe frame
- Cat 1, 3 Point w/Cat.2 Bushings (on some models)
- ◊ Cat 1 QH adaptable
- Ocast Iron Star tines
- ♦ Reversible
- Distributes and pulverizes manure, seed bed prep, renovate pastures, horse arenas, ballfields, levels mole hills, etc.



Model	Description	Tines	Fold	Transport Width	Weight (lbs.)	List Price
WH06	6' Pasture Harrow	Cast Iron	Manual	4' 3"	275 lbs.	\$1,030
WH7.5	7.5' Pasture Harrow	Cast Iron	Manual	4' 7"	296 lbs.	\$1,170
WH13	13' Pasture Harrow	Cast Iron	Manual	7'3"	507 lbs.	\$2,520
WH20	20' Pasture Harrow	Cast Iron	Hyd.	7'3"	811 lbs.	\$4,410

### **CHAIN HARROWS**







### DRAG HARROWS-BARS ONLY

Model	Description	Recommended Sections	Weight (lbs.)	List Price
24-110487	4' Bar	ONE 4' x 4' section	22	\$115
24-110488	6' Bar	ONE 6' x 8' section	33	\$155
24-110489	8' Bar	TWO 4' x 8' sections	43	\$200
24-110490	10' Bar	TWO 10' x 4' sections	54	\$275
24-110491	12' Bar	TWO 6' x 8' sections	64	\$295
DRAG HARROW	S-SECTION ONLY	1		
24-202111	4' x 4' >	(1/2" chain	75	\$274
24-202112	4' x 8' >	(1/2" chain	133	\$500
24-202113	6' x 8' >	(1/2" chain	216	\$765
24-202114	10' x 4'	x 1/2" chain	179	\$695
24-202115	10' x 8'	x 1/2" chain	358	\$1215
3-POINT FRAM	ES (Carrying frame or	nly. Drawbar and Sections	NOT INCLUDED)	
Model	Des	cription	Weight (Ibs.)	List Price
BHL6/8	6'/8' 3-Pt. Mo	unted Harrow Lift	144	\$1,150
BHL10	10' 3-Pt. Moi	unted Harrow Lift	150	\$1,250
BHL12	12' 3-Pt. Moı	unted Harrow Lift	180	\$1,450
ATV HARROWS-	-COMPLETE			
ATV4	4' ATV N	Mini Harrow	105	\$375

ATV6

Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.

165

\$555

6' ATV Mini Harrow

# FINISHING MOWERS

Keep your grassy areas looking good with the 100 Series Economy Finishing Mower by Tar River Implements. These mowers are great for compact tractors maintaining home estates and light landscaping. Available in working widths of 58", 71" and 82".

All Mowers come standard with safety chains. The BFM-107 model comes standard with front anti-scalp roller.



### **Specifications:**

- ◊ Solid Rubber Tires
- ♦ Rear Discharge
- Floating Hitch
- ◊ Easy Cutting Height Adjustment
- ◊ Easy Belt Tension Adjustment

- Over Coat Paint
- ◊ Category 1 Hitch
- O BFM-105 & BFM-106, 3mm deck
- OBFM-107, 4mm deck
- 2 Belt Cutting System

Model	Working Width	Overall Width	HP	Number of Blades	Grass Discharge	Tires	Ship Weight (Ibs.)	List Price
BFM-105	58"	59"	15-30	3	Rear Discharge	Solid Rubber	435	\$1,755
BFM-106	71"	72"	15-30	3	Rear Discharge	Solid Rubber	544	\$2,135
BFM-107	82"	86"	25-50	3	Rear Discharge	Solid Rubber	639	\$2,675

# 3 PT. FLAIL MOWERS

Tar River Implements proudly offers versatile 3-point mounted flail mower models designed to tackle a wide range of mowing applications with ease and efficiency. For smaller tractors, the TREF Sub-Compact Series is the perfect fit—engineered for tractors up to 25 HP, delivering reliable performance in a compact package. For those requiring a bit more power, the TRMF Compact Series is built for tractors up to 45 HP, offering enhanced durability and cutting capacity. Available in cutting widths ranging from 53" to 77", both models are built with rugged construction and European-inspired design, making them ideal for everything from grassy fields to light brush. Whether you're maintaining pastures, orchards, or roadside ditches, Tar River flail mowers are ready to handle all your mowing needs with precision and dependability. *Optional : Y blades available through Parts Department.* 



#### 15-25 **TREF-053** 53" Center 453 **TREF-061** 61" 20-25 485 Center COMPACT FLAIL MOWERS 61" 25-45 670 **TRMF-061** Center **TRMF-077** 77" 756 30-45 Center

62

Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.

\$2,790

\$3,425

\$3.925

# 3 PT. FLAIL MOWERS SECOND FORZA

Introducing the new line of FORZA flail mowers—European-built and backed by decades of manufacturing experience. The COMET Series is designed for compact tractors under 35 HP and is available in 51" and 61" cutting widths, making it ideal for property maintenance, orchards, and vineyards. Joining the lineup is the GALAXY, formerly known as our trusted FLM model, now refreshed with new paint and FORZA branding. Built for larger tractors up to 60 HP, the GALAXY comes in 71" and 81" cutting widths, with the 81" model featuring standard hydraulic offset for added versatility. Both series reflect FORZA's long-standing commitment to quality and performance in every pass.



Model	HP Rating	Working Width	Hitch	Mount	Cutting Cap.	Belts	Blades Weight Ibs.		List Price
Comet-51	18-35	51"	Cat 1	Center	5/8"	3	"Hammer"	408	\$4,115
Comet-61	20-35	61"	Cat 1	Center	5/8"	3	"Hammer"	440	\$4,245

Galaxy-71	30-60	71"	Cat 1-2	Center	3-1/4"	4	"Hammer"	922	\$4,455
Galaxy-87H	35-60	87"	Cat 1-2	15.75" Hyd. Offset	3-1/4"	4	"Hammer"	1,060	\$5,375

# **DITCHBANK MOWERS**



The Tar River hydraulic offset pivoting ditch bank mower is the ideal machine to maintain ditches or embankments around your property. The mount is just like a standard 3 point flail mower but when in full operating position this unit will also mow vertically up to 90° and down to 30/35°. All models come standard with heavy hammer knives and a perfectly balanced rotor for a smooth operation. *Optional : Y blades available through Parts Department.* 









MODEL	A	В	С	D	E	F	G	н	L	М	Р	ANGLE UP	ANGLE DOWN
TRDB-053	17	70	59	54	64	77	20	28	5	32	61	90°	30°
TRDB-061	17	78	67	62	64	85	24	28	5	32	61	90°	30°
TRBD-069	18	98	77	69	69	93	26	30	6	37	71	90°	35°

Model	Working Width	Cutting Angle	MIN HP	Weight (lbs.)	List Price		
LIGHT DUTY							
TRDB-053	53"	90°Up & 30°Down	30	664	\$4,255		
TRDB-061	61"	90°Up & 30°Down	35	697	\$4,435		
MEDIUM DUTY							
TRDB-069	69"	90°Up & 35°Down	45	1,002	\$5,525		

# **DITCHBANK MOWERS**



The FORZA line of ditchbank mowers delivers rugged performance and European-made quality you can count on. Superiorly designed and built for your tough ditchbank mowing conditions. A heavy frame and smoother operating hydraulics will make your life immensely better in maintaining your uneven mowing needs. 3 or 4 belt drives will keep you mowing and minimize slippage in tough conditions. SABRE model is built for small compact tractors, the KATANA for medium compact tractors and the RAPIER for larger more commercial applications. Hammer Blades on all models.



Model	HP Rating	Working Width	Hitch	Slope Angle	Cutting Cap.	Belts	Weight Ibs.	List Price	
LIGHT DUTY	LIGHT DUTY								
Sabre-51	18-35	51"	Cat. 1	190°/ ↓40°	1"	3	550	\$5,755	
Sabre-61	20-35	61"	Cat. 1	1¢90°/↓40°	1"	3	585	\$6,185	
MEDIUM DU	ΓY								
Katana-65	35-65	65"	Cat 1-2	<u>†</u> 90°∕ ↓40°	1-1/2"	3	816	\$7,530	
HEAVY DUTY	HEAVY DUTY								
Rapier-71	50-100	71"	Cat 2	1⁄90°/↓40°	3-1/4"	4	1,874	\$13,760	
Rapier-80	55-100	80"	Cat 2	190°/↓40°	3-1/4"	4	1,984	\$14,310	

# **ROTARY CUTTERS - ECONOMY**





Designed to help dealers compete with the big box stores, Tar River Implements introduces the ERC Rotary Cutters. These mowers have front & rear chains standard, are built for 20-55 HP tractors and have a 3 Year Gearbox Warranty (1 year on the rest). They come with shear-pin or slip-clutch driveline protection, cut capacity of 1 1/2", pan-type stump jumpers and in working widths of 4', 5' and 6'.

#### **Specifications:**

- 45 HP Gearbox
- Shear Pin PTO on 4' Slip Clutch Standard on 5' & 6'
- ◊ 4' 12 GA Deck
- ◊ 5' 11 GA Deck
- ◊ 6' 9 GA Deck

- ◊ Cat. 1 Hitch w/ Floating Top Link
- ♦ 1 1/2" Cutting Capacity
- ◊ Laminated Wheels & Re-greaseable Hubs
- Pan Stump Jumper
- ◊ Safety Chain Shields Standard

Model	Working Width	PTO Protection	Min. HP	Weight (lbs.)	List Price		
ERC-4	48"	Shear-Pin	20	411	\$1,595		
ERC-5SC	60"	Slip Clutch	25	499	\$1,920		
ERC-6SC	72"	Slip Clutch	35	734	\$2,620		
OPTIONAL EQUIPMENT							
COM-147650	\$170						



The Standard Duty Series Rotary Cutter is ideal for mowing backfields, trails, and wildlife paths. It cuts grass, stalks, and brush up to 1" thick with a 12GA, 7.5" deep deck. Adjustable tailwheel allows cutting heights from 1.5" to 9". Heat-treated blades pivot on a steel stump jumper for obstacle protection. A 45 HP cast iron gearbox with forged steel gears includes shear bolt driveline protection. Fits 18–65 HP tractors and is quick hitch compatible. Optional front rubber and rear metal guards available.

Model	Working Width	PTO Protection	Min. HP	Weight (lbs.)	List Price			
ARC48SP	48"	Shear-Pin	18-32	350	\$2,135			
ARC60SP	60"	Shear-Pin	20-50	530	\$2,275			
ARC60SC	60"	Slip Clutch	20-50	530	\$2,575			
ARC72SC	72"	Slip Clutch	25-65	623	\$3,025			
OPTIONAL EQUIPME	OPTIONAL EQUIPMENT							
ARC00148	4' Front Rubber Gu	\$115						
ARC00160	5' Front Rubber Gu	\$130						
ARC00172	6' Front Rubber Gu	\$160						
ARC00589	4' Front Chain Guar	\$230						
ARC00590	4' Rear Chain Guard	\$205						
ARC00591	5' Front Chain Guar	\$280						
ARC00592	5' Rear Chain Guard	\$240						
ARC00593	6' Front Chain Guar	\$335						
ARC00594	6' Rear Chain Guard	d w/ Hardware			\$260			

# ROTARY CUTTERS - MEDIUM DUTY





Tar River Implements proudly introduces the MRC and HRC Series Rotary Cutters—rugged and reliable solutions for landowners and professionals alike.

Engineered for performance and durability, these rotary mowers are designed to work with tractors ranging from 40 to 90 horsepower. Both the MRC and HRC models come standard with front and rear chain shielding for added safety and protection during operation.

Built to tackle tough mowing conditions, these cutters feature a heavy-duty slip-clutch PTO for added driveline protection and a 2-inch cutting capacity, making them ideal for managing thick grass, brush, and light saplings.

Each unit is backed by an industry-leading 5-Year Gearbox Warranty, ensuring peace of mind and long-term value in the field.



#### **Specifications:**

- O HP Gearbox
- 2" Cutting Capacity
- Laminated Wheels & Re-greaseable Hubs
- Solid Stump Jumper
- ◊ 7" Sides MRC-6 8" Sides HRC-7

- Ock Thickness 3mm & 5mm
- A Replaceable Skids
- ♦ Safety Chain Shields Standard
- Cat.1 MRC-6 Cat.2 HRC-7
- MRC-6 one tailwheel & HRC-7 two tail wheels

Model	Working Width	PTO Protection	Min. HP	Tail Wheels	Weight (lbs.)	List Price
MRC-6	72"	Slip Clutch	40-90	1	725	\$3,310
HRC-7	84"	Slip Clutch	50-90	2	1,375	\$4,340

# ROTARY CUTTERS - MEDIUM DUTY

The ARC Medium Duty Rotary Cutters are ideal for backfields, trails, and wildlife paths. The 6' model cuts up to 1" thick brush with an 11GA, 7.5" deep deck; the 7' model cuts up to 2" thick with a 10GA, 9.8" deep deck and reinforced 3/16" sides. Cutting height adjusts from 1.5"–11" via a laminated tailwheel (dual on 7'). Heat-treated blades pivot on a heavy-duty stump jumper to protect the gearbox. Both models feature a cast iron gearbox with forged gears and slip clutch protection. The 6' comes with Cat. 1 clevis pins; the 7' fits Cat. 1 & 2. Quick Hitch compatible and suited for 28–65 HP (6') and 45–90 HP (7'). Standard chain guards included.

### AVAILABLE IN GREY ONLY



Model	Working Width	PTO Protection	Min. HP	Tail Wheels	Weight (Ibs.)	List Price
ARCMD72	72"	Slip Clutch	28-65	Single	761	\$3,550
ARCMD84	84"	Slip Clutch	45-90	Dual	1,100	\$5,625



ickئlick Hitch

# **SPREADERS - PULL TYPE**





Built with steel gears, this ground drive unit will hold up to the rigors of your everyday needs. Adjustable tow bar allows the spreader to be used on a multiple hitch height configurations. High floatation tires on a wide base give greater stability over many types of terrain.

 $\Diamond$ 

#### **Specifications:**

♦ Heavy duty steel gears in gearbox

- Left center right spread pattern
- Optional spread deflector shield available

- Adjustable towing hitch
   High floatation tires
- Over coated frame and hopper or Poly hopper

Model	Capacity (Ibs.)	Capacity (Cu. Ft.)	Spread Swath	Hopper	Hopper Height	Tires	Weight (Ibs.)	List Price
PTS-100	225	3.7	20'	Metal	40"	13" x 6"	75	\$675
PTS-100P	225	3.7	20'	Poly	40"	13" x 6"	70	\$775
PTS-160	360	5.3	20'	Metal	44"	16 <sup>1</sup> / <sub>2</sub> " x 8"	82	\$895
PTS-160P	360	5.3	20'	Poly	44"	16 <sup>1</sup> / <sub>2</sub> " x 8"	76	\$975
BG-800	1,885	27.5	52'	Metal	34"	20 x 10.0 x 8"	419	\$2,950
OPTIONAL EQUIPMENT								
PTS-001 Deflector Shield							\$85	
PTS-002	Cable Gate	\$300						

 

 Spreader Assembly
 \$35 (dealer net)

 Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.

# SPREADERS - 3 POINT



High-quality spreaders with special heat-treated paint that resists rust. Easy and quick assembly, available in Poly and Steel hoppers.

#### **Specifications:**

- ◊ Cat.1 three point hitch
- Opendable Gearbox
- ◊ Fixed Agitator (Optional Roller Wheel Agitator)
- Sturdy Metal Hopper With Special Heat-Treated Paint To Resist Rust

MPLEMEN

Poly hopper with Stainless steel bottom and spreading fins

Model	Capacity lbs.	Capacity Cu. Ft	Hopper Height	Spread Swath	Weight (lbs.)	List Price			
STEEL HOPPER	STEEL HOPPER								
SSS-300	716	8.6	40"	46'	115	\$875			
SSS-500	1,058	12	46"	46'	133	\$925			
POLY HOPPER W	ITH STAINLESS S	TEEL BOTTOM AN	D FINS (PLASTIC (	ON SSC MODEL)					
SSC-100	224	Cat. 0 & 1	23'	31'	83	\$795			
SP-300SS	716	8.6	42"	46'	127	\$980			
SP-500SS	1,121	12	46"	46'	135	\$1.020			
OPTIONAL EQUIPMENT									
ARS-12		\$80							
	Spreader Assembly (2 = free assembly)								

# SPREADERS - SIDE SHOT



Designed for precise spreading of fertilizer and salt or sand. The material shoots out of the sides making it a perfect tool for winery/vineyards, blueberry farms, Christmas tree farms or anywhere else precise application is necessary.

"Side-Shot" components can be removed to use the spreader as any typical 3-Point mounted Fertilizer Spreader.

#### **Specifications:**

- Designed for spreading fertilizer and salt
- Material shoots out of both left and right sides
- Standard Grate Filter & Hydraulic Lever Control for Spreader Gate

Category 1 & 2 Hitch
 Stainless Steel Bottom

Model	Max Capacity	Spread Swath	Unit Dimensions (H x W)	Weight (lbs.)	List Price			
SR-600	1,719 lbs.	26' - 59'	38" x 51"	229	\$2,995			
SR-800	2,204 lbs.	26' - 59'	40" x 55"	264	\$3,215			
OPTIONAL EQUIPMENT								
SR-002	\$170							
## **SPREADERS - PENDULAR**





Designed to provide excellent precision while at the same time being versatile enough to spread materials with different weights, textures, and sizes as well as high-moisture materials (up to 30% moisture content) such as powdered fertilizer.













3 Possible Spread Patterns



Model	Max Capacity	Spread Swath		Weight (Ibs.)	List Price
SPT0-350	795 lbs.	39' - 46' Granulated	16' - 19' Powdered	203	\$2,950
SQTF-600	1,402 lbs.	39' - 46' Granulated	16' - 19' Powdered	322	\$3,650
SQTF-1000A	2,645 lbs.	39' - 46' Granulated	16" - 19" Powdered	344	\$4,215
OPTIONAL EQUIPM	ENT				
SQTF-001	Salt & Sand Chu	te			\$190
SQTF-002	Rubber Chute In	sert			\$75
SQTF-003	Hydraulic Lever	Control			\$430
SQTF-004	Agitator Extensio	n			\$100
SQTF-005	Grate Filter		\$170		
	Spreader Assem	\$50 (dealer net)			

## LANDSCAPE RAKES





Add the finishing touch to your yard or work space. The Tar River Implements STR Series Landscape Rake is available in 4' - 8' working widths to fit most tractor needs. Tine stiffener comes standard.

Model	Working Width	HP Range	Weight (lbs.)	List Price
STR-4	48"	18-45	242	\$1,155
STR-5	60"	20-45	291	\$1,240
STR-6	72"	25-45	348	\$1,360
STR-7	84"	30-45	395	\$1,490
STR-8	96"	35-45	448	\$1,680

## REAR BLADES OF THE TAR RIVER



### **MED. DUTY**

Tar River Implements offers a full line of rear blades to fit your needs. From the Light Duty 60" blade for simple grading jobs all the way up to the 6-way Heavy Duty with Hydraulic Tilt, Angle and Offset in an 9' version for your toughest jobs.

Model	Working Width	M.Board Height	M.Board Thickness	M.Board Offset	M.Board Angle & Tilt	Max HP	Weight (Ibs.)	List Price	
STANDARD DU	TY ECONOMY	- UP TO 40 H	IP - TILT & A	NGLE					
BRB-205	60"	14"	1/4"	N/A	Yes	40	190	\$690	
BRB-206	72"	14"	1/4"	N/A	YES	40	216	\$795	
MEDIUM DUTY ECONOMY - UP TO 60 HP - TILT, ANGLE & OFFSET									
BRB-506	72"	13"	1/4"	Yes	Yes	60	333	\$1,335	
BRB-507	84"	13"	1/4"	Yes	Yes	60	355	\$1,395	
BRB-508	96"	13"	1/4"	Yes	Yes	60	377	\$1,455	
6-WAY HEAVY I	outy - up to 9	90 HP - HYD. /	ANGLE, MANU	JAL TILT & OF	FSET STANDAR	RD			
BRB-907	84"	19"	1/4"	Yes	Yes	90	908	\$2,995	
BRB-908	96"	19"	1/4"	Yes	Yes	90	939	\$3,450	
BRB-909	108"	19"	1/4"	Yes	Yes	90	979	\$3,640	
OPTIONAL EQU	IPMENT								
BRB-009HC Hydraulic Cylinder Kit for Tilt (on BRB-9 Series)								\$625	

## **DISC HARROWS**









Tar River Implements offers a range of Disc Harrows in different sizes to suit your needs. The DHC model is suitable for compact tractors up to 35 hp, featuring 16" notched blades. This series has 7 1/2" disc spacing and 1" square high strength axle re-greaseable flange bearings.

The DHS models are ideal for tractors with 25-50 hp. All units come with adjustable gang angles and are compatible with Category 1&2 quick hitch. Standard features include 18" notched blades, a sturdy main frame made of heavy duty 2 3/8" square tubing, and gangs with 1" square high strength axle re-greaseable flange bearings.

Model	Cutting Width	Spacing	Disc Size	# of Discs	HP	Weight (lbs.)	List Price	
COMPACT SERIES								
DHC-4816	4'	7 1/2"	16"	12	15-35	430	\$1,450	
DHC-6016	5'	7 1/2"	16"	16	15-35	496	\$1,675	
STANDARD SE	RIES							
DHS-4818	4'	7 1/2"	18"	12	25-35	630	\$2,425	
DHS-6018	5'	7 1/2"	18"	16	35-45	818	\$2,785	
DHS-7418	6'2"	7 1/2"	18"	20	45-50	904	\$3,165	
DHS-9020	7' 6"	9"	18"	20	50-60	970	\$3,475	

## CULTIPACKER

DIAMOND DISCOUNT STRUCTURE

Qປick

Hitch

Compatible

Tar River Implements now has four sizes of Cultipackers available for your landscaping needs.

Designed for 18-40 hp tractors. They are made with a 2" square tube main frame. The packer wheels are 9 1/2" cast iron steel. Category 1 quick hitch compatible.



Model	Working Width	HP	Weight (lbs.)	List Price
CP-48L	48"	18-40	364	\$2,226
CP-60L	60"	18-40	439	\$2,469
CP-72L	72"	18-40	509	\$2,763
CP-84L	84"	18-40	578	\$3,096

### CULTIVATORS & PLOWS



The Tar River Implements Spring Loaded Cultivators are available in three sizes. They come in 36", 54" and 72" working widths and are made using 3/8" Steel angle iron with 3/4" wide shanks.





#### **Specifications:**

- $\diamond$ Suitable for stone and root filled soil: light and medium soil conditions
- Used for loosening and aerating soil up to 9 inches  $\Diamond$ below the surface
- Prepares seedbeds guickly and economically  $\Diamond$
- When one tine strikes a hidden obstruction the  $\Diamond$

others continue to work at the correct depth. Strength derived from heavy duty shanks, which  $\Diamond$ once fixed to the frame cannot move or strain out of position  $\diamond$ 

- Shovel to Shovel Distance 15"
- $\Diamond$ Height 21"

Model	Spring	Tines	Total Length	Working Width	Tractor Power (HP)	Weight (Ibs.)	List Price	List Price 2 Pack (same model in sets of 2)
SLC-5			50"	36"	15-45	260	\$1,195	\$1,095
SLC-7	3/8" x 50"	3/8" x 2 1/2"	68"	54"	30-45	396	\$1,595	\$1,495
SLC-9			86"	72"	40-45	482	\$1,895	\$1,795

## **CULTIVATORS & PLOWS**









PB1

AMBP22

#### Sub-Soiler / Middle Buster

- ◊ Cat. 1 Hitch
- Over Coat Paint
- ♦ Adjustable Ripping/Digging Depth
- Heavy-Duty Steel Frame with Ripper Tooth (Sub-Soiler) and 14" Middle Buster

#### **3 Point Cultivator**

- ♦ Adjustable Shank width
- 6 Reversible heat-treated shovels
- ◊ Welded steel angle frame
- ♦ Category 1 hitch pin
- A Recommended for tractors less than 50 HP

#### Hiller/Ripper

- ♦ Heavy Duty Construction (*HKCI*)
- ◊ 18" Discs
- ◊ Adjustable Row Width
- \*\*A-HKC1 Ripper Accessory sold separately List Price — \$85

#### 1 & 2 Bottom Plows

- 1 Bottom Plow (PB1) with a 14" Bottom
- 2 Bottom Plow (AMBP22) with 14" Bottoms

Model	Description	Hitch	Misc. Info	Weight (lbs.)	List Price
BSM-100	Sub-Soiler / Mid Buster Combo	Cat. 1		79/88	\$340
TPC-6	3 Point Cultivator	Cat. 1	49" Width	96	\$425
HKC1	Hiller/Ripper	Cat. 1		192	\$1,190
PB1	1 Bottom Plow	Cat. 1	14" Bottom	186	\$1,415
AMBP22	2 Bottom Plow	Cat. 1	14" Bottoms	479	\$2,075

The 100 Series 4' Box Blade is the go-to tool for working gravel, topsoil, mulch, and manure. Its 4 ripper shanks on a 2×4" steel beam adjust to three depth levels, with 6" reversable and replaceable front and rear blades. An 18" box depth and 12.75" moldboard height provide solid capacity. Cat. 1 and Quick Hitch compatible, it suits tractors 15–28 HP.

ickئlick Hitch

**BOX BLADES** 

The 200 Series Box Blade handles tougher grading, ruts, washouts, and driveway leveling. It features five or six 4-position heavy-duty ripper shanks on a rigid 4" square tube beam with 5/16" side plates. The 22" box depth and 16.95" moldboard adds capacity, while the rear blade , which is replaceable and reversable, can push material in reverse. Cat. 1 and Quick Hitch compatible, it's ideal for 18–45 HP tractors and available in 5' and 6' models.



Model	Working Width	Side Plate Thickness	A-Frame Thick- ness	# Shanks	Max HP	Weight (Ibs.)	List Price
100 SERIES							
ABB148	48"	1/4"	3/8"	4	15-28	245 lbs.	\$1,055
200 SERIES							
ABB260	60"	5/16"	1/2"	5	18-35	395 lbs.	\$1,335
ABB272	72"	5/16"	1/2"	6	20-45	445 lbs.	\$1,560



QUICK Hitch Compatible

Tar River Implements has Box Blades available in eight popular sizes. The Sub-Compact Box Blades come in 48" and 60" working widths and 1/4" side plates. The Medium Duty Box Blades come in 60" and 72" working widths with 3/8" side plates for 60" model and 1/2" side plates for the 72". Our heavier duty 84" and 96" working widths come with 1/2" side plates and a sturdy A-Frame to get the job done. Clevis hitches and durable design for the Tar River Box Blades make them a great tool for all around dirt maintenance.

The front and rear replaceable 6" scraper blades allow for quick and easy replacement making the Tar River line of box blades an excellent choice for all your dirt moving needs!





\* TRBS—GREY ONLY

Model	Working Width	Side Plate Thickness	Clevis Hitch	# Shanks	Max HP	Weight (lbs.)	List Price
SUB-COMPAC	T MODELS						
TRBS4	48"	1/4"	Cat 1	4	24	326 lbs.	\$990
TRBS5	60"	1/4"	Cat 1	5	24	379 lbs.	\$1,055
BB4SC	48"	1/4"	Cat 1	4	24	343 lbs.	\$1,020
BB5SC	60"	1/4"	Cat 1	5	24	390 lbs.	\$1,120
MEDIUM DUT	Y MODELS						
BB5	60"	3/8"	Cat 1	5	50	502 lbs.	\$1,330
BB6	72"	1/2"	Cat 1	6	50	548 lbs.	\$1,540
HEAVY DUTY N	MODELS						
BBXD7	84"	1/2"	Cat 1 & 2	7	60	639 lbs.	\$1,715
BBXD8	96"	1/2"	Cat 1 & 2	8	60	730 lbs.	\$1,915

## LAND LEVELER WITHOUT SHANKS 😉

Quick Hitch

Compatible Tar River 5' and 6' Land Grader is designed with two parallel grading blades positioned at a 10 degree angle. Both 0.375" x 6" high carbon heat-treated blades are reversible and replaceable. It features adjustable skid shoes and boasts a durable frame construction. The 5' and 6' land graders are Cat 1, quick hitch compatible, and ideally suited to tractors 25-55 HP (see specs below). The 8' land grader comes standard with Cat 1-2 Clevis style hitch pins.



#### Specifications:

- $\diamond$ Cat. 1 Quick Hitch Adaptable 60" & 72"
- Cat. 1 & 2 Quick Hitch Adaptable 96"  $\diamond$

 $\diamond$ **Clevis Hitch** 

- Adjustable Grading Height  $\Diamond$
- $\Diamond$ Adjustable Skid Shoes

Model	Working Width	HP	Weight (lbs.)	List Price
ALG260	60"	25-50	430	\$1,995
ALG272	72"	30-55	465	\$2,295
ALG396	96"	40-90	582	\$2,450

### LAND LEVELER WITH SHANKS





Scarifier shanks (standard) and grading blades are multi-adjustable.



#### **Specifications:**

- ◊ Cat. 1 Quick Hitch Adaptable
- ◊ Cat 1 & 2 QH Adaptable on LB6 & LB7
- ◊ Clevis Hitch

- ◊ Adjustable Grading Height & Ripping Shanks
- A Replaceable Skid Shoes
- Scarifier Shanks come standard

Model	Working Width	Max HP	Ripping Shanks	Weight (lbs.)	List Price
LB4	48"	50	4	455	\$1,655
LB5	60"	50	5	589	\$1,940
LB6	72"	50	6	700	\$2,190
LB7	84"	50	7	759	\$2,395

## WOOD CHIPPERS OF TAR RIVER

Hitch

Compatible

The Tar River Wood Chipper is the perfect tool to help you clear your land of fallen limbs and branches. Use your wood chips to create beautifully covered flowerbeds and natural areas in the yard. Wood chips not only look nice, but they also help regulate soil temperature, retain moisture and even improve plant growth by helping release necessary nutrients into the soil.

The BWC-040EC is a manual feed chipper. It is PTO driven and available in a 4" chipping capacity.

The BWC-H Series are Self-Contained Hydraulic Feed Chippers. This series is available in 4", 6", and 8" chipping capacities. These chippers come equipped with internal hydraulic pumps that are run by the tractor PTO and require no external hydraulic feed.

Introducing the BWC-07DH to the Tar River Implements line of chippers. This chipper is a self contained Dual Hydraulic Roller Feed chipper. It has a 7" chipping capacity but a larger opening on the chute.



### WOOD CHIPPERS OF BLOOD





Built In Temperature Gauge on BWC-07DH

Model	Chipping Capacity	HP	Chipper Wheel	Discharge Hood Height	Weight (lbs.)	List Price			
MANUAL FEED									
BWC-040-M	4"	18-35	24.8" / 99 lbs.	65"	507	\$2,625			
SELF-CONTAINED H	SELF-CONTAINED HYDRAULIC FEED W/ PTO								
BWC-040-H	4"	18-35	18.5" / 55 lbs.	74"	584	\$4,390			
BWC-060-H	6"	25-60	24.8" / 128 lbs.	83"	794	\$4,995			
BWC-080-H	8"	35-80	24.7" / 131 lbs.	81"	891	\$5,995			
DUAL-HYDRAULIC F	DUAL-HYDRAULIC ROLLER FEED								
BWC-07DH	7"	40-80	29.1" / 187 lbs.	89"	1,234	\$7,395			

# EP/ERP

### **Mechanical Winches**





#### STANDARD PROPORTIONAL BRAKE

provides a precise control over the wire rope release speed, preventing jerking on the winch and tractor, as well as unnecessary loosening of the wire rope on the drum

#### PYRAMID SUPPORTING STRUCTURE

All control assemblies are installed inside. Clutch and brake control mechanisms are protected from external factors and damage.



Slider Rotating V Veriga II Slider Rotating POK II



Patented Stop Switch



Patented Central Lubrication Spray System



Patented Lower Pulley with closing hatch and axially movable chain wheel

	KRPAN 4 EP	KRPAN 5 ERP	KRPAN 6 ERP
Pulling Capacity (kN)	35	45	55
Brake Capacity (kN)	43,8	56,3	68,8
Average Winching Speed (m/s)	0,9	0,6	0,6
Number of Clutch Plates	1	3	3
Standard Wire Rope Length/Wire Rope ø (m/ mm)	70/8	70/9	80/10
Maximum Wire Rope Length/Wire Rope ø (m/ mm)	100/8	130/9	100/10
Recommended Tractor Power(kW/HP)	22-35 kW / 30-48 HP	28-50 kW / 38-68 KM	33-55kW / 45-75 KM
Operation	Mechanical	Mechanical	Mechanical
Width (mm)	1222	1418	1618 / *1818
Depth (mm)	450	550	550
Height with Wire Guard (mm)	2028	2310	2310
Height without Wire Guard (mm)	1465	1531	1531
Weight without Wire Rope (kg)	260	398	408
Mounting Category	l.	I., II.	I., II.
Proportional Brake	Std	Std	Std
Bottom Pulley	Std	Std	Std

Model	Pulling Capacity	Breaking Capacity	HP	Wire Rope Dia.	Wire Rope Length.	Weight (without Wire Rope) (Ibs.)	List Price
MECHANICAL WINCHES							
4EP	35 kN	43.8kN	30-48	8mm	229'	635	\$3,990
5ERP	45kN	56.3kN	38-68	9mm	229'	957	\$5,125
6ERP	55 kN	68.8kN	45-75	10mm	262'	1,014	\$6,070
OPTIONAL EQUIPMENT							
Slider Rotating POK II Slider Rotating POK - Standard Duty					\$65		

# HYDRAULIC WINCHES OF THE KRPAN

### **Electro Hydraulic Forestry Winches**





#### PATENTED UPPER HYDRAULIC PULLEY

with patented STOP switch and improved wire rope guidance which holds the wire rope always under tension.

**PATENTED LOWER PULLEY WITH A CLOS-ING HATCH** prevents wire rope from falling out.

**PATENTED CENTRAL LUBRICAION SYSTEM** for spray lubrication.

PATENTED AXIALLY MOVABLE CHAIN WHEEL allows for longer clutch life

**PATENTED CHAINSAW HOLDER** with 90degree rotation for easier access



Upper Hydraulic Pulley



Bottom Pulley w/ Stop Switch



Central Lubrication System



Axially Moveable Chain Wheel



**Chainsaw Holder** 

	KRPAN 6EH	KRPAN 7EH	KRPAN 9EHP
Pulling Capacity (kN)	55	65	85
Brake Capacity (kN)	68,8	81,3	106,3
Average Winching Speed (m/s)	0,6	0,6	0,6
Number of Clutch Plates	3	5	5
Standard Wire Rope Length/Wire Rope ø (m/mm)	80/10	80/11	100/13
Maximum Wire Rope Length/Wire Rope ø (m/mm)	100/10	120/11	110/13
Recommended Tractor Power(kW/HP)	33-55kW / 45-75 HP	44-70kW / 60-95 HP	> 59kW / >80 HP
Operation	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic
Width (mm)	1618	1718	1818
Depth (mm)	550	660	700
Height with Wire Guard (mm)	2310	2315	2335
Height without Wire Guard (mm)	1531	1770	1790
Weight without Wire Rope (kg)	463	630	700
Mounting Category	I., II.	II., III.	11. , 111.
Bottom Pulley	Std.	Std.	Std.
STOP Switch - Upper Pulley	Std.	Std.	Std.
Hydr. Pulley	Std.	Std.	Std.
Rope Speed Valve	Std.	Std.	Std.
Radio Remote Control	Std.	Std.	Std.
Radio Remote Ctrl with Proportional Brake	N/A	N/A	Std.

Model	Pulling Capacity	Breaking Capacity	HP	Wire Rope Dia.	Wire Rope Length.	Weight (lbs.)	List Price	
HYDRAULIC	HYDRAULIC WINCHES							
6EH	35 kN	43.8kN	30-48	10mm	80mt	1,140	\$12,250	
7EH	45kN	56.3kN	38-68	11mm	100mt	1,559	\$13,950	
9EHP	55 kN	68.8kN	80 +	13mm	100mt	1,750	\$16,950	
OPTIONAL EQUIPMENT								
Slider Rotating V Veriga II Slider Rotating V Veriga - Heavy Duty						\$65		

## **POST HOLE DIGGER**



New Sub Compact model available

### **STAND AND** LEVELER STANDARD!

Tar River Implements introduces the BPH-100 and BPHSC-100 3pt Post Hole Digger. Equipped with a Category 1 hitch and an 15-60 HP rated gearbox. Now standard with a stand and leveler. Three choices of augers, BPH-06A is a 6", BPH-09A is a 9" and the BPH-12A is a 12".

Model	Description	HP	Hitch	Weight (Ibs.)	List Price
POST HOLE DIG	GER				
BPHSC-100	Sub-Compact PHD	15-30	Cat 1	157	\$1,045
BPH-100	Post Hole Digger	18-60	Cat 1	157	\$1,195
AUGERS					
BPHSC-06A	6" Auger 32" Overall Leng	gth		20	\$150
BPHSC-09A	9" Auger 32" Overall Leng	gth		31	\$195
BPHSC-12A	12" Auger 32" Overall Leng	12" Auger 32" Overall Length			
BPH-06A	6" Auger 48" Overall Len	6" Auger 48" Overall Length			
BPH-09A	9" Auger 48" Overall Len	35	\$205		
BPH-12A	12" Auger 48" Overall Len	oth		49	\$285

per crate sizes can be mixed (additional cost il purchased individually) achageu z

### **TRACTOR TOOLS**



#### 3 Pt. Bale Spear

- ◊ Standard 49" Spear
- ◊ 2,000 lb. Capacity
- Cat. 1 Hitch Pins

#### **Trailer Mover**

- Designed to Move Empty Trailers with the Tractor's 3-Pt Hitch
- ♦ Category 1 Hitch (*TM1&TM2*)
- ◊ Trailer Ball & Receiver not Included

#### 3-Point 1200 lb. Pallet Fork

- Designed to carry 1200 lbs.
- ◊ Cat. 1 Hitch
- $\diamond$  26" High Frame and 46" Forks

#### Clamp on Bucket Forks

- $\diamond$  2000 lbs. carrying capacity per pair
- ♦ Fork Dimensions 4" x 2" x 44"





Model	Description	Hitch	Misc. Info.	Weight (lbs.)	List Price
TPS1	Bale Spear - 3 Pt. Mount	Cat. 1	2,000 lb. Cap.	85	\$425 (\$375 5 pack discount)
TM1	Trailer Mover SD	Cat. 1	2"x2" Post	35	\$275 (\$200–5 pack discount)
TM2	Trailer Mover HD	Cat. 1	3.2" x 3.2" Post	56	\$320 (\$245–5 pack discount)
PF	46" 3-Pt. Pallet Fork	Cat. 1		106	\$385
BFT2000	44" Clamp-on Bucket Forks	N/A		108/pair	\$425 (Pair)

### TRACTOR TOOLS



#### **Quick-Hitch Adapters**

- Attach To Tractor For Quick & Easy Hook-Up For 3-Pt Implements
- Category 1 (QH1) or Category 2 (QH2) Adapters Available
- ◊ Heavy-Duty Steel

#### **3 Point Rear Weight Bracket**

- ♦ Cat.1
- Quick hitch adaptable.
- ♦ 3 3/16" square tubing
- ♦ Fits up to 8 suitcase wts.
- ◊ 2 5/16" Ball
- ♦ 2" receiver
- ♦ 3/8" recovery hook

#### <u>3 Point Rear Weight Bracket w/Quick</u> <u>Htich on Rear</u>

- ◊ Cat.1 adaptable in Front
- ♦ Cat. 1 QH in rear
- ♦ 3 3/16" square tubing
- ♦ Fits up to 8 suitcase wts.
- ◊ 2 5/16" Ball
- 0 2" receiver
- $\diamond$  3/8" recovery hook
- PERFECT for the QH compatible Tar River Drills



Model	Description	Hitch	Weight (lbs.)	List Price
QH1	Cat. 1 Adapter	Cat. 1	67	\$250
QH2	Cat. 2 Adapter Max 100HP	Cat. 2	132	\$390
RWB-1	3 pt. Rear Weight Bracket	Cat. 1	66	\$350
RWB-QH	3 pt. Rear Weight Bracket w/ Quick HItch	Cat. 1	121	\$575

OPTIONAL	OPTIONAL EQUIPMENT					
QHA-1KIT	Quick Hitch Bushing Set—Cat. 1 (Parts Discount)	\$25				
QHA-2KIT	Quick Hitch Bushing Set—Cat. 2 (Parts Discount)	\$28				
QHA-25	Quick Hitch 1 Adapter Bracket (Parts Discount)	\$25				
QHA-35	Quick Hitch 2 Adapter Bracket (Parts Discount)	\$30				

### TAR RIVER ATTACHMENTS NOTES AND GENERAL INFORMATION





- Standard Mounting is Universal Skid Steer Mount (except when noted otherwise)
  - ♦ Euro/Global optional at additional costs—use prefix "EG".
  - JD Mounts optional at additional costs—use prefix "JD". Mounts fit these loaders:
    - ◊ 200X, 200CX, 210, 300, 300X, 300CX, 400, 400X, 400CX, 520, 521, 540, 541, 542
- Hydraulic Hoses & Flat Faced Couplers come standard when necessary with all units except when noted otherwise.

## PALLET FORKS - BUCKETS - GRAPPLES

PALLET FORKS						
Model	Description	Loader	Capacity	Fork Lengths	Weight	
SCPF	Sub Compact	Sub-Compact	900 lbs.	36" or 42"	190 lbs 205 lbs.	
CPF	Compact	Compact	2,000 lb. & 3,000 lb.	42" - 48"	235 lbs 274 lbs.	
EPF	Economy	Compact or Utility	4,200 lb.	48"	395 lbs.	
MPF	Medium Duty	Utility or Larger	4,200 lb.	42" or 48"	376 lbs 394 lbs.	
HPF	Heavy Duty	Utility or Larger	5,200 lb.	48" or 60"	414 lbs 460 lbs.	
WTPF & WTHPF	Walk Through	Skid Steer	4,200# & 5,200 lb.	42" - 48" - 60"	378 lbs 394 lbs.	
HYPF	Hyd. Side Shift	Utility or Larger	4,200 lb.	48"	436 lbs.	

BUCKETS				
Model	Description	Typical Uses		
RB	Rock Bucket	Essential attachment for separating rocks from dirt as well as for clearing and building sites. Ideal for sifting out large rocks and debris. Catches rocks 3" plus.		
LP	Low Profile Bucket	High visibility specifically designed for skid steer loaders. For general purpose grading and moving dirt.		
LB	Long Bottom Bucket	Built heavy for large skid steer applications. An excellent attachment for precise grading and construction purposes. 35 1/2" deep to allow for easy view of front edge while working.		
CU	Compact Utility Bucket	All around general purpose specifically made for tractor loaders.		
XMB	Material Bucket	Material /Snow / Litter bucket is used for moving litter, chips, snow and other light material.		
4N1	4-IN-1 Bucket	Multi-purpose bucket for grappling, dozing, backfilling , loading, digging and fine grading		
DB	Disbursement Bucket	Bucket attachment for carrying concrete, filling grain feeders, moving gravel and dirt. .85 Yard struck Capacity		
HDB	High Dump Bucket	This bucket allows an extra 3 feet of dumping height for full loading capacity of truck or spreader.		
HDGB	Grapple Bucket	Multi-purpose tool combining bucket and grapple		
SB	Stump Bucket	Attachment bucket designed to dig around stumps with its narrow cutting surface for easy stump removal. Great for digging narrow ditches for footings or storm ditches.		

	GRAPPLES					
Model	Description	Typical Uses				
RG	Rock Grapple	A fundamental implement for separating rocks from dirt as well as for contractors clearing a lot for site building. It is also essential for storm damage clean up. The Rock Grapple is ideal for sifting out large rocks and debris. It is excellent in pastures, lawns or construction sites. It will catch any rock or piece of debris that is larger than 3 inches				
SBG	Stump Bucket Grapple	Used for prying and removing stumps with the gripping power to secure the load				
RG	Root Grapple	Moving logs, brush, rocks or many other types of debris. Available in single and double grapple configurations CRG (< 40 HP) HDRG1 (35-50 HP) HDRG2 (40-60HP) XRG (60+ HP)				
BG	Brush Grapple	Deigned for tearing into roots, trash and rubbish and loading the debris into trucks or wagons. Designed to roll debris into tight piles.				
HFG	Fork Grapple	An essential tool on the farm, logging and construction industry. Great for moving logs, fence posts, pipes and debris.				
FG	Log Grapple	Unique rounded tine design to easily hold large logs, pipes, fence posts and culverts.				
94	Prices and spe	cifications subject to change without notice. Check discounts & availability before quoting.				

Product Designs May Differ Slightly Than What Appears in the Photographs.

### SUB-COMPACT PALLET FORKS

- Iight, Durable Frame & Forks great for Sub-Compact Tractors
- ◊ SCPF36 = 900 lbs. Lift Capacity 36" forks
- SCPF42 = 900 lbs. Lift Capacity 42" forks
- COMPACT PALLET FORKS

Standard Universal Skid Steer Mount

#### Available in Domestic and Import

♦ Light, Durable Frame & Forks great for Compact Tractors

MEDIUM & HEAVY DUTY PALLET FORKS

♦ 4.200 Lift Capacity

- ◊ CPF42 = 2,000 lbs. Lift Capacity 42" forks
- ◊ CPF48 = 3,000 lbs. Lift Capacity 48" forks
- Standard Universal Skid Steer Mount

EPF SERIES	<ul> <li>4,200 Lift Capacity</li> <li>48" Forks</li> <li>Standard Universal Skid Steer Mount</li> <li>Optional JD Mount Available</li> </ul>	
MPF & HPF SERIES	<ul> <li>Use The Same Heavy Built Frames</li> <li>Frames Are Rated For Up To 5,500 lbs.</li> <li>The Only Difference Between The MPF &amp; HPF are the Fork Ratings</li> <li>The Same Applies For the Walk-Thru Forks</li> </ul>	MPES
MPF SERIES	<ul> <li>4,200 lbs. Lift Capacity</li> <li>42" &amp; 48" Forks Available</li> <li>Walk-Thru Frames Available as WTPF Series</li> <li>Standard Universal Skid Steer Mount</li> <li>Optional JD &amp; Euro/Global Mounts Available</li> </ul>	
HPF	<ul> <li>5,200 lbs. Lift Capacity</li> <li>48" &amp; 60" Forks Available</li> <li>Walk-Thru Frames Available as WTHPF Series</li> </ul>	

Standard Universal Skid Steer Mount

♦ Optional JD & Euro/Global Mounts Available

SERIES

### PALLET FORKS









95



EPF SERIES

### PALLET FORKS



Model	Description	Capacity	Mount	Weight	List Price
SUB COMPA	CT FORKS - 900 LBS.				
SCPF36	Sub Compact Pallet Forks - 36" Forks	900 lbs.	Uni. Skid Steer	161 lbs.	\$575
JDSCPF36	Sub Compact Pallet Forks - 36" Forks	900 lbs.	JD 200/300	150 lbs.	\$575
SCPF42	Sub Compact Pallet Forks - 42" Forks	900 lbs.	Uni. Skid Steer	171 lbs.	\$595
JDSCPF42	Sub Compact Pallet Forks - 42" Forks	900 lbs.	JD 200/300	160 lbs.	\$595
COMPACT F	ORKS - 2,000 LBS. & 3,000 LBS.				
CPF42	Compact Pallet Forks - 42" Forks	2,000 lbs.	Uni. Skid Steer	253 lbs.	\$675
JDCPF42	Compact Pallet Forks - 42" Forks	2,000 lbs.	JD 200/300 and 400/500	253 lbs.	\$675
CPF48	Compact Pallet Forks - 48" Forks	3,000 lbs.	Uni. Skid Steer	274 lbs.	\$815
JDCPF48	Compact Pallet Forks - 48" Forks	3,000 lbs.	JD 200/300 and 400/500	274 lbs.	\$815
CPF42-USA	US Frames Compact Pallet Forks - 42"	2,000 lbs.	Uni. Skid Steer	253 lbs.	\$775
CPF48-USA	Compact Pallet Forks - 48"	3,000 lbs.	Uni. Skid Steer	274 lbs.	\$895
MEDIUM DU	ITY FORKS - 4,200 LBS.				
MPF42	Medium Duty Forks - 42" Forks	4,200 lbs.	Uni. Skid Steer	376 lbs.	\$1,150
EGMPF42	Medium Duty Forks - 42" Forks	4,200 lbs.	Euro/Global	376 lbs.	\$1,150
JDMPF42	Medium Duty Forks - 42" Forks	4,200 lbs.	JD 200/300 and 400/500	376 lbs.	\$1,150
MPF48	Medium Duty Forks - 48" Forks	4,200 lbs.	Uni. Skid Steer	394 lbs.	\$1,175
EGMPF48	Medium Duty Forks - 48" Forks	4,200 lbs.	Euro/Global	394 lbs.	\$1,175
JDMPF48	Medium Duty Forks - 48" Forks	4,200 lbs.	JD 200/300 and 400/500	394 lbs.	\$1,175
EPF48	Med. Duty Cage Design- 48" Forks	4,200 lbs.	Uni. Skid Steer	395 lbs.	\$995
JDEPF48	Med. Duty Cage Design- 48" Forks	4,200 lbs.	JD 200/300 and 400/500	395 lbs.	\$995
HEAVY DUTY	( FORKS - 5,200 LBS.				
HPF48	Heavy Duty Forks - 48" Forks	5,200 lbs.	Uni. Skid Steer	414 lbs.	\$1,210
EGHPF48	Heavy Duty Forks - 48" Forks	5,200 lbs.	Euro/Global	414 lbs.	\$1,210
JDHPF48	Heavy Duty Forks - 48" Forks	5,200 lbs.	JD 200/300 and 400/500	414 lbs.	\$1,210
HPF60	Heavy Duty Forks - 60" Forks	5,200 lbs.	Uni. Skid Steer	460 lbs.	\$1,285
EGHPF60	Heavy Duty Forks - 60" Forks	5,200 lbs.	Euro/Global	460 lbs.	\$1,285
	1		JD 200/300 and		1

\*\*\*\*

### PALLET FORKS () INCOME

### HYDRAULIC PALLET FORKS

- Same Frame as our MPF48 but with welded-on 48" forks that can be moved hydraulically from side to side
- Available in 48" forks, 4,200 lbs. forks only
- Ounits Come Standard With Flat Faced Couplers & Hoses
- ◊ Standard Universal Skid Steer Mount
- Optional JD or Euro/Global Mounts





#### WALK THRU PALLET FORKS

- ♦ 4,200 lbs. Lift Capacity
   WTPF Series ♦ 42" & 48" Forks Available
   ♦ Standard Universal Skid Steer Mount
  - ◊ 5,200 lbs. Lift Capacity
- WTHPF Series <sup>()</sup> 48" & 60" Forks Available
  - Standard Universal Skid Steer Mount

Model	Description	Capacity	Mount	Weight	List Price
WALK-THRU M	IEDIUM DUTY FORKS - 4,200 LBS.				
WTPF42	Walk-Thru Med. Duty Forks - 42"	4,200 lbs.	Uni. Skid Steer	378 lbs.	\$1,150
WTPF48	Walk-Thru Med. Duty Forks - 48"	4,200 lbs.	Uni. Skid Steer	396 lbs.	\$1,175
WALK-THRU I	HEAVY DUTY FORKS - 5,200 LBS.				
WTHPF48	Walk-Thru Heavy Duty Forks - 48"	5,200 lbs.	Uni. Skid Steer	416 lbs.	\$1,210
WTHPF60	Walk-Thru Heavy Duty Forks - 60"	5,200 lbs.	Uni. Skid Steer	462 lbs.	\$1,285
HYDRAULIC F	PALLET FORKS				
HYPF48	Hydraulic Shift Pallet Forks - 48"	4,200 lbs.	Uni. Skid Steer	436 lbs.	\$2,475
HYPF60	Hydraulic Shift Pallet Forks - 60"	4,200 lbs.	Uni. Skid Steer	493 lbs.	\$2,585

Z	Model	Size (in.)		List Price Per Tine
D	COM-111802 - SCPF, JDSCPF	1 x 3 x 36	2A	\$110
	COM-111803 - SCPF, JDSCPF	1 x 3 x 42	2A	\$120
Ĭ	COM-90222 – CPF, JDCPF	1.18 x 3 x 42	2A	\$135
	COM-80489 - CPF/JD, EFP/JD, MPF/JD/EG, WTPF	1.38 x 4 x 48	2A	\$215
TZ	COM-83801 - HPF/JD/EG, WTHPF	1.5 x 4 x 48	2A	\$235
NES	COM-87132 - HPF/JD/EG, WTHPF	1.5 x 4 x 60	2A	\$305
()	COM-401830 - OPTIONAL	1.5 x 4 x 72	2A	\$375



### BALE SPEARS

### LOADER MOUNT BALE SPEARS

**EBS Series** -

- $\Diamond$ Standard Universal Skid Steer Mount Only
- $\diamond$ Single Spear Configuration Only
- $\Diamond$ 49" Spear
  - $\Diamond$ 2,800 lbs. capacity
  - $\Diamond$ Standard Universal Skid Steer Mount
  - $\Diamond$ Optional JD & Euro/Global Mounts Available
  - $\Diamond$ Hi-Back Configurations Available (HBS Series)
- BS Series ◊ Single, Double & Triple Spear Configurations Available
  - $\Diamond$ Standard 49" Spear
  - $\Diamond$ 3,500 lbs. capacity



Description	Capacity	Mount	Weight	List Price						
LOADER MOUNT - SINGLE SPEAR										
Quick-Attach Bale Spear - 49"	2,800 lbs.	Uni. Skid Steer	157 lbs.	\$695						
Lo-Back Bale Spear - Single 49"	3,500 lbs.	Uni. Skid Steer	189 lbs.	\$765						
Lo-Back Bale Spear - Single 49"	3,500 lbs.	Euro/Global	189 lbs.	\$880						
Lo-Back Bale Spear - Single 49"	3,500 lbs.	JD	189 lbs.	\$880						
Γ - DOUBLE SPEAR										
Lo-Back Bale Spear - Double 49"	3,500 lbs.	Uni. Skid Steer	233 lbs.	\$895						
Lo-Back Bale Spear - Double 49"	3,500 lbs.	Euro/Global	233 lbs.	\$1,010						
Lo-Back Bale Spear - Double 49"	3,500 lbs.	JD	233 lbs.	\$1,010						
LOADER MOUNT - TRIPLE SPEAR										
Lo-Back Bale Spear - Triple 39"	3,500 lbs.	Uni. Skid Steer	291 lbs.	\$925						
Lo-Back Bale Spear - Triple 39"	3,500 lbs.	Euro/Global	291 lbs.	\$1,040						
Lo-Back Bale Spear - Triple 39"	3,500 lbs.	D	291 lbs.	\$1,040						
	SINGLE SPEAR     Quick-Attach Bale Spear - 49"     Lo-Back Bale Spear - Single 49"     Lo-Back Bale Spear - Single 49"     Lo-Back Bale Spear - Single 49"     Lo-Back Bale Spear - Double 49"     Lo-Back Bale Spear - Double 49"     Lo-Back Bale Spear - Double 49"     Lo-Back Bale Spear - Triple 39"     Lo-Back Bale Spear - Triple 39"	A SINGLE SPEARQuick-Attach Bale Spear - 49"2,800 lbs.Lo-Back Bale Spear - Single 49"3,500 lbs.Lo-Back Bale Spear - Double 49"3,500 lbs.Lo-Back Bale Spear - Triple 39"3,500 lbs.Lo-Back Bale Spear - Triple 39"3,500 lbs.	A SINGLE SPEARQuick-Attach Bale Spear - 49"2,800 lbs.Uni. Skid SteerLo-Back Bale Spear - Single 49"3,500 lbs.Uni. Skid SteerLo-Back Bale Spear - Single 49"3,500 lbs.Euro/GlobalLo-Back Bale Spear - Single 49"3,500 lbs.JDF DOUBLE SPEAR3,500 lbs.Uni. Skid SteerLo-Back Bale Spear - Double 49"3,500 lbs.Uni. Skid SteerLo-Back Bale Spear - Double 49"3,500 lbs.Euro/GlobalLo-Back Bale Spear - Double 49"3,500 lbs.JDLo-Back Bale Spear - Triple 39"3,500 lbs.Uni. Skid SteerLo-Back Bale Spear - Triple 39"3,500 lbs.Euro/Global	SINGLE SPEARQuick-Attach Bale Spear - 49"2,800 lbs.Uni. Skid Steer157 lbs.Lo-Back Bale Spear - Single 49"3,500 lbs.Uni. Skid Steer189 lbs.Lo-Back Bale Spear - Single 49"3,500 lbs.Euro/Global189 lbs.Lo-Back Bale Spear - Single 49"3,500 lbs.JD189 lbs.Lo-Back Bale Spear - Single 49"3,500 lbs.JD189 lbs.Lo-Back Bale Spear - Single 49"3,500 lbs.JD189 lbs.Lo-Back Bale Spear - Double 49"3,500 lbs.Uni. Skid Steer233 lbs.Lo-Back Bale Spear - Double 49"3,500 lbs.Euro/Global233 lbs.Lo-Back Bale Spear - Double 49"3,500 lbs.JD233 lbs.Lo-Back Bale Spear - Triple 39"3,500 lbs.Uni. Skid Steer291 lbs.Lo-Back Bale Spear - Triple 39"3,500 lbs.Euro/Global291 lbs.						

98



### **BALE GRABBERS & UNWINDERS**



### **BALE GRABBERS**

#### RBG Series - For Round Bales (opens 48" - 78")

- ◊ Available with 1 or 2 Hyd. Cylinders
- Available in Universal Skid Steer or Euro/Global Mounts
- ◊ Circular Design Ensures Strong & Gentle Grip of Bale
- Loader Mount Legs Provide Easy Hook-Up/Disconnect
- Units Come Standard With Hydraulic Hoses -No Couplers



**RBG SERIES** 



**SBG SERIES** 

SBG Series - For Square/Round Bales (opens 26"-80")

- Comes Standard with 2 Hyd. Cylinders
- Available in Universal Skid Steer or Euro/Global Mounts
- Loader Mount Legs Provide Easy Hook-Up/Disconnect
- Units Come Standard With Hydraulic Hoses No Couplers

Model	Description	Capacity	Mount	Weight	List Price	Packed			
ROUND BALE GRABBER									
RBG-101	Round Bale Grabber - 1 Cydr.	2,200 lbs.	Uni. Skid Steer	430 lbs.	\$2,680	3			
RBG-102	Round Bale Grabber - 1 Cydr.	2,200 lbs.	Euro/Global	430 lbs.	\$2,680	3			
RBG-201	Round Bale Grabber - 2 Cydr.	2,200 lbs.	Uni. Skid Steer	446 lbs.	\$2,925	з			
RBG-202	Round Bale Grabber - 2 Cydr.	2,200 lbs.	Euro/Global	446 lbs.	\$2,925	3			
SQUARE B	ALE GRABBER								
SBG-201	Square Bale Grabber - 2 Cydr.	2,200 lbs.	Uni. Skid Steer	661 lbs.	\$2,475	1			
SBG-202	Square Bale Grabber - 2 Cydr.	2,200 lbs.	Euro/Global	661 lbs.	\$2,475	1			



RBU S◊Hydrauli◊3 Bale S	c Bale Unwinder	<ul> <li>3 point and University</li> <li>mount</li> <li>3 point and Europe</li> </ul>		
Model	Description	Mount	Weight	List Price
ROUND BA	LE UNWINDER			
RBU-100	Round Bale Unwinder	Skid Steer & 3 pt.	353 lbs.	\$3,320
RBU-101	Round Bale Unwinder	Euro Global & 3 pt.	353 lbs.	\$3,320

### BUCKETS E KOUNT

<u>C(</u>	OMPAC	T UTILITY BUCKET			and the second second	
$\diamond$	Great Fo	or Compact Tractors	a de la constante			
$\diamond$	19" Higł	h x 18" Deep				
$\diamond$	4" x 1/2	2" Cutting Edge				
$\diamond$		Durable Construction				
$\diamond$	•	s below 45 HP				
0		d Universal Skid Steer Mount	64			
Ô		I JD Mount				
	Available	e Sizes: 48", 60" & 72" 👘 🌈				S AND A CONTRACT OF
<b>\</b>	Available		UB	SEKIEDA		
	Model	Description	Struck Capacity	SER ESS Mount	Weight	List Price
	Model	U		Mount	Weight	List Price
C	Model	Description		Mount	Weight 157 lbs.	List Price
C	Model OMPACT UT	Description	Capacity			
C(	Model OMPACT UT CUB48	Description	Capacity .22 <sup>3</sup>	Universal Skid Steer	157 lbs.	\$895
	Model OMPACT UT CUB48 CUB60 CUB72 EAST SI	Description TILITY BUCKET Compact Utility Buckets - 48" Compact Utility Buckets - 60"	Capacity .22 <sup>3</sup> .27 <sup>3</sup>	Universal Skid Steer Universal Skid Steer	157 lbs. 201 lbs.	\$895 \$995

- ♦ A-36 Steel with 3/4" x 6" cutting edge
- ◊ 1/4" Wrap & 1/2" Wall
- $\diamond$  1/2" Wear Bars and Side Cutters
- ◊ 21 3/4" High x 37.9" Deep
- ◊ Weld-On & Bolt-On Teeth Available
- ◊ Heavy, Durable Construction
- ◊ Standard Universal Skid Steer Mount
- ◊ Available Sizes: 72",78" & 84"

Т



Model	Description	Struck Capacity	Mount	Weight	List Price
BEAST SERIE	S				
BB72	Beast Series – 72"	1.16 <sup>3</sup>	Universal Skid Steer	776 lbs.	\$2,375
BB72T	Beast Series – 72" w/ teeth	1.16 <sup>3</sup>	Universal Skid Steer	826 lbs.	\$2,705
BB78	Beast Series —78"	1.23 <sup>3</sup>	Universal Skid Steer	815 lbs.	\$2,675
BB78T	Beast Series –78" w/ teeth	1.23 <sup>3</sup>	Universal Skid Steer	865 lbs.	\$2,880
BB84	Beast Series – 84"	1.36 <sup>3</sup>	Universal Skid Steer	875 lbs.	\$2,975
BB84T	Beast Series – 84" w/ teeth	1.36 <sup>3</sup>	Universal Skid Steer	932 lbs.	\$3,215
OPTIONAL					
EG	Euro-Global Mount instead of Sk	kid Steer Mount (factor	y welded)		\$115
JD	JD Mount instead of Skid Steer	Mount (factory welded)	· · ·		\$115
BOSS2	Optional Side Cutters—BEAST BL	JCKET (Set of 2)			\$165
100					

### BUCKETS E

### SERIOUS DUTY MATERIAL BUCKET

- Ideal For Litter, Snow, Manure and Other Large Volume/ Light Weight Materials (NOT for digging)
- ♦ A-36 Steel with 3/4" x 6" cutting edge
- ◊ 28" High x 36" Deep
- ◊ Weld-On & Bolt-On Teeth Available
- Heavy, Durable Construction Standard Universal Skid Steer Mount
- ◊ Optional JD or Euro/Global Mounts
- Available Sizes: 80", 90" & 96"



### XMB SERIES

Model	Description	Struck Capacity	Mount	Weight	List Price
SERIOUS DU	TY MATERIAL				
XMB80	Serious Duty Material Bucket - 80"	1.21 <sup>3</sup>	Universal Skid Steer	710 lbs.	\$1,940
XMB90	Serious Duty Material Bucket - 90"	1.36 <sup>3</sup>	Universal Skid Steer	825 lbs.	\$2,195
XMB96	Serious Duty Material Bucket - 96"	1.45 <sup>3</sup>	Universal Skid Steer	920 lbs	\$2,315
<ul> <li>A-36 Ste</li> <li>3/16" W</li> <li>21" High</li> <li>Weld-On</li> <li>Heavy, D</li> <li>For units</li> <li>Standard</li> </ul>	ROFILE BUCKET el with 3/4" x 6" cutting edg rap & 1/2" Wall x 27.5" Deep & Bolt-On Teeth Available urable Construction below 67 HP d Universal Skid Steer Mount e Sizes: 60", 72", & 84"			LP S	ERIES
Model	Description	Struck Capacity	Mount	Weight	List Price
LOW PROFILI					
LP60	Low Profile Bucket – 60"	0.37 <sup>3</sup>	Universal Skid Steer	307 lbs.	\$1,235
LP66	Low Profile Bucket – 66"	0.41 <sup>3</sup>	Universal Skid Steer	345 lbs.	\$1,335
LP72	Low Profile Bucket – 72"	0.45 <sup>3</sup>	Universal Skid Steer	369 lbs.	\$1,435

LP84	Low Profile Bucket – 84"	0.52 <sup>3</sup>	Universal Skid Steer	455 lbs.	\$1,630		
PREFIX	OPTIONAL						
EG	Euro-Global Mount instead of Ski	Euro-Global Mount instead of Skid Steer Mount (factory welded)					
JD	JD Mount instead of Skid Steer M	JD Mount instead of Skid Steer Mount (factory welded)					
BOCE12	Bolt on cutting edge for Buckets v	with Bolts (install	ed)		\$495		

### BUCKETS

### LONG BOTTOM BUCKET

- Long Bottom, Low Profile Bucket  $\Diamond$
- A-36 Steel with 3/4" x 6" cutting edge  $\Diamond$
- 3/16" Wrap & 1/2" Wall  $\Diamond$
- $\diamond$ 21" High x 33.5" Deep
- Weld-On & Bolt-On Teeth Available  $\Diamond$
- $\diamond$ Heavy, Durable Construction
- For units below 67 HP  $\Diamond$
- Standard Universal Skid Steer Mount  $\Diamond$
- Available Sizes: 60", 72", & 84"  $\diamond$



Model	Description	Struck Capacity	Mount	Weight	List Price					
LONG BOTTO	ONG BOTTOM									
LB60	Long Bottom Bucket - 60"	0.37 <sup>3</sup>	Universal Skid Steer	481 lbs.	\$1,310					
LB72	Long Bottom Bucket - 72"	0.45 <sup>3</sup>	Universal Skid Steer	537 lbs.	\$1,555					
LB84	Long Bottom Bucket - 84"	0.52 <sup>3</sup>	Universal Skid Steer	651 lbs.	\$1,815					

### **ROCK BUCKET**

- 3/4" x 6" cutting edge  $\Diamond$
- 3/8" tines across bottom spaced 3" apart  $\diamond$
- $\diamond$ High Quality 1/2" A36 Steel
- Weld-On Teeth Optional  $\diamond$
- Heavy, Durable Construction  $\diamond$
- Standard Universal Skid Steer Mount  $\Diamond$
- Optional JD or Euro/Global Mounts  $\diamond$
- Available Sizes: 60", 72", 84" & 96"  $\diamond$



#### Model shown with optional teeth

Model	Description	Mount	Weight	List Price
ROCK BUCKET				
RB60	Rock Bucket — 60"	Universal Skid Steer	605 lbs.	\$1,815
RB72	Rock Bucket — 72"	Universal Skid Steer	720 lbs.	\$2,025
RB84	Rock Bucket – 84"	Universal Skid Steer	822 lbs.	\$2,305
RB96	Rock Bucket – 96"	Universal Skid Steer	942 lbs.	\$2,595

PREFIX	OPTIONAL	List Price	
EG	Euro-Global Mount instead of Skid Steer Mount (factory welded)	\$115	
D	JD Mount instead of Skid Steer Mount (factory welded)	\$115	
102	Prices and specifications subject to change without notice. Check discounts & availability before quoting.		

Product Designs May Differ Slightly Than What Appears in the Photographs.

### ROCK GRAPPLE E SECON

### **ROCK GRAPPLE**

- ♦ 3/4" x 6" cutting edge
- 3/8" tines across bottom and 1/2" sides spaced 3" apart
- $\diamond$  1/2" top tines on grapple
- ♦ Twin Cylinders with 2" bore & 10" stroke
- ♦ High Quality 1/2" A36 Steel

- $\diamond$  1 1/4" pins with counter sunk grease fittings
- Weld-On Teeth Optional
- ♦ Heavy, Durable Construction
- Units Come Standard With Flat Faced Couplers & Hoses
- ◊ Standard Universal Skid Steer Mount
- ◊ Optional JD or Euro/Global Mounts
- Available Sizes: 60", 72", 84" & 96"



Model shown with optional teeth

Model	Description	Mount	Weight	List Price
ROCK GRAPPLE				
RG60	Rock Grapple – 60"	Universal Skid Steer	778 lbs.	\$4,250
RG60T	Rock Grapple – 60" w/ weld on teeth	Universal Skid Steer	818 lbs.	\$4,365
RG72	Rock Grapple – 72"	Universal Skid Steer	920 lbs.	\$4,750
RG72T	Rock Grapple $-72"$ w/ weld on teeth	Universal Skid Steer	960 lbs.	\$4,995
RG80	Rock Grapple – 80"	Universal Skid Steer	940 lbs.	\$4,995
RG80T	Rock Grapple – 80" w/ weld on teeth	Universal Skid Steer	1,000 lbs.	\$5,295
RG84	Rock Grapple – 84"	Universal Skid Steer	1,087lbs.	\$5,085
RG84T	Rock Grapple – 84" w/ weld on teeth	Universal Skid Steer	1,127 lbs.	\$5,395

PREFIX	OPTIONAL	List Price
EG	Euro-Global Mount instead of Skid Steer Mount (factory welded)	\$115
JD	JD Mount instead of Skid Steer Mount (factory welded)	\$115

## UTILITY ROOT GRAPPLES OF STATE

Specially designed for tractors and utility work. Heavy built, but still light weight to not overpower your tractor lift capabilities. All Compact Root Grapples come standard with hoses and Pioneer Couplers. All Standard Duty Root Grapples come standard with hoses and Flat-Faced Couplers. Available in JD and Euro Mounts.

	COMPACT	STANDARD DUTY
HP Rating	Under 40	Under 50
Frame	3" x 3"	3" x 3"
Tines	3/8"	3/8"
Spacing	10"	9 1/4"
Max Opening	34"	35"
Depth	29"	35 1/2"
Height Closed	16"	15 <sup>1</sup> / <sub>2</sub> "
Cylinders	2" x 8"	2" x 10"
Widths	48" - 60" - 72"	60" - 66" - 72"



Model	Description	Mount	Weight	List Price	Packed (same size)			
SUB COM	SUB COMPACT ROOT GRAPPLE - TRACTOR LOADER USE ONLY							
SCRG48	Sub Compact Root Grapple - Single Grapple - 48"	Uni. Skid Steer	250 lbs.	\$1,760	2			
COMPACT	ROOT GRAPPLE - TRACTOR LOADER USE ONLY							
CRG48	Compact Root Grapple - Single Grapple - 48"	Uni. Skid Steer	420 lbs.	\$1,794	2			
CRG60	Compact Root Grapple - Double Grapple - 60"	Uni. Skid Steer	438 lbs.	\$2,054	2			
CRG66	Compact Root Grapple - Double Grapple - 66"	Uni. Skid Steer	465 lbs.	\$2,147	2			
CRG72	Compact Root Grapple - Double Grapple - 72"	Uni. Skid Steer	487 lbs.	\$2,262	2			
STANDARI	D DUTY ROOT GRAPPLE - TRACTOR LOADER US	E ONLY						
SDRG260	Standard Duty Root Grapple—Double Grapple—60"	Uni. Skid Steer	600 lbs.	\$3,195	2			
SDRG266	Standard Duty Root Grapple—Double Grapple—66"	Uni. Skid Steer	625 lbs.	\$3,265	2			
SDRG272	Standard Duty Root Grapple—Double Grapple—72"	Uni. Skid Steer	650 lbs.	\$3,325	2			
PREFIX	OPTIONAL							
JD	JD Mount instead of Skid Steer Mount (factory	welded)		\$	115			

### COMMERCIAL ROOT GRAPPLES

Heavy designed for higher HP tractors and skid steer for intense commercial applications. Commercial Root Grapples come standard with hoses and Flat Faced Couplers. Available in JD and Euro Mounts.

	HEAVY DUTY	SERIOUS DUTY
HP Rating	Under 65	65+
Frame	4" x 4"	4" x 4"
Tines	1/2"	<sup>1</sup> / <sub>2</sub> " Inside - <sup>5</sup> / <sub>8</sub> " Outside
Spacing	9 1/2"	9"
Max Opening	34"	37"
Depth	34 1/2"	37 1/2"
Height Closed	17"	16 <sup>1</sup> /2"
Cylinders	2" x 10"	2" x 10"
Widths	72" - 80"	72" - 80"



Model	Description	Mount	Weight	List Price
HEAVY DUT	Y ROOT GRAPPLE - TRACTOR LOADER OR SKID STEER USE			
HDRG272	Heavy Duty Root Grapple – Double Grapple – 72"	Universal Skid Steer	749 lbs.	\$3,650
HDRG280	Heavy Duty Root Grapple — Double Grapple — 80"	Universal Skid Steer	769 lbs.	\$3,850
HDRG284	Heavy Duty Root Grapple – Double Grapple –8 4"	Universal Skid Steer	825 lbs.	\$3,945
SERIOUS D	UTY ROOT GRAPPLE - TRACTOR LOADER OR SKID STEER US	SE		
XRG72	Serious Duty Root Grapple - Double Grapple - 72"	Universal Skid Steer	930 lbs.	\$4,255
XRG80	Serious Duty Root Grapple - Double Grapple - 80"	Universal Skid Steer	960 lbs.	\$4,375
XRG84	Serious Duty Root Grapple - Double Grapple - 84"	Universal Skid Steer	1,010 lbs.	\$4,675
PREFIX	OPTIONAL			
EG	Euro-Global Mount instead of Skid Steer Mount (factory we	elded)		\$115
DL	JD Mount instead of Skid Steer Mount (factory welded)			\$115

### CLAW GRAPPLES (S) STORE (S

### CLAW GRAPPLE - AR400

- ♦ Made With 3/8" AR400 Steel
- ◊ Cylinder has 2" bore & 10" stroke
- ◊ Units Come Standard With Pioneer Couplers & Hoses
- ◊ Universal Skid Steer Mount & JD Mount
- Oual Cylinders
- ♦ 55" & 66" Working Widths
- **OBUILT FOR SUB-COMPACT TRACTORS ONLY**





### STD DUTY CLAW GRAPPLE

- Cylinder has 2 1/2" bore & 8" stroke
- Units Come Standard With Pioneer Couplers & Hoses
  - Universal Skid Steer Mount
  - Dual Cylinders
  - 60", 66" & 72" Working Widths

Model	Description	Width	Mount	Weight	List Price	Packed (same size)	
COMPACT CLA	COMPACT CLAW GRAPPLE - AR 400 STEEL - UNDER 25 HP - TRACTOR LOADER USE ONLY						
CCG55-AR	Compact Claw Grapple 55" with AR400 Steel	55"	Uni. Skid Steer	205 lbs.	\$1,925	2	
JDCCG55-AR	Compact Claw Grapple 55" with AR400 Steel	55"	John Deere Mount	192 lbs.	\$1,925	2	
CCG66-AR	Compact Claw Grapple 66" with AR400 Steel	66"	Uni. Skid Steer	220 lbs.	\$2,075	2	
JDCCG66-AR	Compact Claw Grapple 66" with AR400 Steel	66"	John Deere Mount	210 lbs.	\$2,075	2	
STANDARD DI	JTY CLAW GRAPPLE UP TO 50 HP - TRACTO	)r loade	R USE ONLY				
SDCG60	Standard Duty Claw Grapple 60"	60"	Uni. Skid Steer	367 lbs.	\$2,210	2	
SDCG66	Standard Duty Claw Grapple 66"	66"	Uni. Skid Steer	387 lbs.	\$2,395	2	
SDCG72	Standard Duty Claw Grapple 72"	72"	Uni. Skid Steer	407 lbs.	\$2,580	2	
106	Driego and anagifications subject to share	do withou	t notice Check	liceounto	<sup>0</sup> availabi	lite . In a fama and	

### CLAW GRAPPLES 😂 🕅



#### HEAVY DUTY STANDING CLAW GRAPPLE

- Heavy Duty Construction 1/2" A-36 Steel
- Cylinders have 2" bore & 10" stroke
- Opens 52" to grab big material and closes tight
- $\diamond$  1 1/4" pins with counter sunk grease fittings and bushings
- Gussets on front tips for extra protection
- $\diamond$  3" x 3" x 1/4" Heavy Duty tubing
- **o** Units Come Standard With Flat Faced Couplers & Hoses
- ◊ Standard Universal Skid Steer Mount
- Optional JD or Euro/Global Mounts
- Available Sizes: 72", 78" & 84"

Model	Description	Mount	Weight	List Price
HEAVY DUTY	STANDING CLAW GRAPPLE			
HDCG72	Heavy Duty Claw Grapple - 72"	Universal Skid Steer	1,033 lbs.	\$4,385
HDCG78	Heavy Duty Claw Grapple - 78"	Universal Skid Steer	1,120 lbs.	\$4,570
HDCG84	Heavy Duty Claw Grapple - 84"	Universal Skid Steer	1,205 lbs.	\$4,905
Prefix	OPTIONAL			
EG	Euro-Global Mount instead of Skid Steer Mount (factor	ry welded)		\$115
D	JD Mount instead of Skid Steer Mount (factory welded	)		\$115

### MISC. GRAPPLES

### FORK GRAPPLE

- Great for the log industry move and carry more  $\diamond$ than regular pallet forks
- Grapple consists of 2" bore and 10" stroke  $\Diamond$ cylinder
- Units Come Standard With Flat Faced Couplers  $\Diamond$ & Hoses
- 48" Forks with 4,200 lbs. capacity  $\Diamond$
- Standard Universal Skid Steer Mount  $\Diamond$
- Optional JD or Euro/Global Mounts  $\Diamond$





### **GRAPPLE BUCKET**

- Heavy Duty Construction 1/4" A-36 Steel  $\diamond$
- Cylinders have 2" bore & 10" stroke  $\diamond$
- $\Diamond$ Heavy Duty Cylinder Covers
- 1 1/4" pins with counter sunk grease fittings and  $\Diamond$ bushings
- Weld-On & Bolt-On Teeth Available  $\Diamond$
- Units Come Standard With Flat Faced Couplers &  $\diamond$ Hoses
- $\diamond$ Standard Universal Skid Steer Mount
- Optional JD or Euro/Global Mounts  $\Diamond$
- Available Sizes: 60", 72", 84" & 96"  $\Diamond$

Model	Description	Mount	Weight	List Price
FORK GRAP	PLE			
HFG48	Heavy Duty Fork Grapple - 48" Forks	Universal Skid Steer	715 lbs.	\$2,965
GRAPPLE BU	ICKET			
HDGB60	Heavy Duty Grapple Bucket - 60"	Universal Skid Steer	820 lbs.	\$3,995
HDGB72	Heavy Duty Grapple Bucket - 72"	Universal Skid Steer	907 lbs.	\$4,195
HDGB84	Heavy Duty Grapple Bucket - 84"	Universal Skid Steer	972 lbs.	\$4,485
HDGB96	Heavy Duty Grapple Bucket - 96"	Universal Skid Steer	1,081 lbs.	\$4,765
Prefix	OPTIONAL			
EG	Euro-Global Mount instead of Skid Steer Mount (factory welded)			
JD Mount instead of Skid Steer Mount (factory welded)			\$115	
BOCE12 Bolt on cutting edge for Buckets with Bolts (installed)				\$495
108 Prices and specifications subject to change without notice. Check discounts & availability before qu				

Product Designs May Differ Slightly Than What Appears in the Photographs.
### **VIBRATORY POST DRIVER**



Tar River Manufacturing Post Drivers are designed to efficiently drive posts and break concrete on your skid steer. The vibratory action makes quick work driving posts into the ground. Both models come with a 8" post pad.

The action of the "jackhammer" drive allows you to drive posts with minimal post splitting common on typical drivers. The cup design of the post pad keeps the post positioned and allows it to be pulled or pushed straight if it begins to angle off course while being driven.



Model	Description	Ft. Ibs. Energy	GPM	Post Pad Size	Mount	Weight	List Price
VIBRATORY POST DRIVER							
PD-68-200	Post Driver	750 lbs.	10.5-19	8"	Uni. Skid Steer	1,200 lbs.	\$5,315
PD-75-240	Post Driver	1,000 lbs.	13-24	8"	Uni. Skid Steer	1,650 lbs.	\$6,255

## LAND PLANE

Grade your land professionally with the Tar River land plane.

Built with heavy steel, this leveler will make short work of your grading needs on your farm, construction site or driveway.

Available in 6 and 8 foot working widths, the TRLP is the ideal tool for tackling many landscaping jobs.



Model	Description	Mount	Weight	List Price
TRLP72	72" Land Plane	Universal Skid Steer	209 lbs.	\$1,470
TRLP84	84" Land Plane	Universal Skid Steer	243 lbs.	\$1,795

110

## HEAVY DUTY BRUSH CUTTER





### HEAVY DUTY BRUSH CUTTER

- $\diamond$  Low-Flow Cutter (14/23)
- Open-Faced, Heavy Duty Deck made with 1/4" A36 Steel
- ♦ 6" Cutting Capacity
- ◊ Hydraulic Direct Drives & Internal Relief Valve
- O Bi-Directional Cutting

- ♦ 3 Cutting Blades (AR-500 steel)
- Units Come Standard With Flat Faced Couplers & Hoses
   Standard Universal Skid Steer Mount
- RECOMMENDED: FLOW 16-20 GPM DO NOT EXCEED 23 GPM

Model	Description	Cutting Capacity	Flow	Mount	Weight	List Price
HEAVY DUTY	(					
TRBC60	5 Foot Heavy Duty Brush Cutter	6"	14-20 gpm	Uni. Skid Steer	1074 lbs.	\$7,440
TRBC70	6 Foot Heavy Duty Brush Cutter	6"	14-20 gpm	Uni. Skid Steer	1530 lbs.	\$7,995

## SERIOUS DUTY BRUSH CUTTER 😂 🕅 🗤



### SERIOUS DUTY BRUSH CUTTER

- ♦ Low-Flow Cutter (16/25)
- Open Faced, Heavy Duty Deck made with 1/4" A36 Steel
- 6" Cutting Capacity
- ◊ Hydraulic Direct Drives & Internal Relief Valve
- O Bi-Directional Cutting
- Extreme Blade Pan That is Extra Large To Maintain Force & Momentum
- ♦ 2 Cutting Blades (AR-500)
- ◊ Units Come Standard With Flat Faced Couplers & Hoses

- Standard Universal Skid Steer Mount
- ♦ Optional JD or Euro/Global Mounts
- ♦ Available Sizes: 60" & 72"

RECOMMENDED: FLOW 16-25 GPM DO NOT EXCEED 28 GPM CALL FOR HIGH FLOW OPTIONS

Model	Description	Mount	Weight	List Price			
SERIOUS DUT	SERIOUS DUTY						
XBC60	Serious Duty Brush Cutter - Low-Flow - 60"	Uni. Skid Steer	1,300 lbs.	\$8,050			
XBC72	Serious Duty Brush Cutter - Low-Flow - 72"	Uni. Skid Steer	1,802 lbs.	\$8,850			
PREFIX	OPTIONAL						
EG	Euro-Global Mount instead of Skid Steer Mount (facto		\$115				
JD	JD Mount instead of Skid Steer Mount (factory welded		\$115				

Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.

# HD STUMP BUCKETS & GRAPPLES 鱼



### HEAVY DUTY STUMP BUCKET

- Angled toward the front to keep the dirt from "sticking" inside the bucket
- **b** Extra Bracing on the Back and Sides of the Bucket
- ♦ 3 Large Pin-On Teeth (Side Pin)
- ♦ 28" Wide across the Back
- ◊ 14" Wide across the Front
- ◊ 33.5" Deep
- 3/4" x 6" Cutting Edge Standard Universal Skid Steer Mount
- Optional JD or Euro/Global Mounts





### HEAVY DUTY STUMP BUCKET GRAPPLE

- ◊ 23" High x 24" Wide
- ◊ 4 Large Pin-on Teeth
- ◊ 3" x 3" Square Tubing
- ♦ 3/4" x 6" Cutting Edge
- 1/2" Gussets all around for added strength and durability
- Protection plates on top and front of grapple
- Grapple opens to 37"
- ◊ 1 1/4" Pins and bushings
- Ounter-sunk grease fittings
- Units Come Standard With Flat Faced Couplers & Hoses
- Standard Universal Skid Steer Mount
- Optional JD or Euro/Global Mounts

Model	Description	Mount	Weight	List Price	
STUMP BUCKET					
SB100	Heavy Duty Stump BucketUniversal Skid Steer310 lbs.			\$1,135	
STUMP BU	CKET GRAPPLE				
SBG100	Heavy Duty Stump Grapple	Universal Skid Steer	402 lbs.	\$1,895	
Prefix	OPTIONAL				
EG	Euro-Global Mount instead of Skid Steer Mount (factory welded)			\$115	
JD	JD Mount instead of Skid Steer Mount (factory welded)				
Prices and specifications subject to change without notice. Check discounts & availability before quoting					

# SD STUMP BUCKETS & GRAPPLES



### SERIOUS DUTY STUMP BUCKET

- Built from 4" x 4" x 1/4" Square Tubing  $\Diamond$
- 1/2" High Quality Steel on Sides, Bottom & Back  $\Diamond$
- 5 ft. 7 inches Deep  $\Diamond$
- 14" Wide across front  $\Diamond$
- $\Diamond$ 20" Wide across back

- $\Diamond$ 3 large replaceable cast teeth
- $\Diamond$ Serrated sides to help break loose roots and other debris
- 1" x 8" cutting edge  $\diamond$
- Standard Universal Skid Steer Mount  $\Diamond$
- Optional JD or Euro/Global Mounts



- Units Come Standard With Flat Faced Couplers & Hoses
- Standard Universal Skid Steer Mount  $\Diamond$
- Optional JD or Euro/Global Mounts Δ

Model	Description	Mount	Weight	List Price		
STUMP BUCKET						
SB200	Serious Duty Stump Bucket Universal Skid Steer 625 lbs.			\$1,545		
STUMP BUG	STUMP BUCKET GRAPPLE					
SBG200	Serious Duty Stump Grapple	Universal Skid Steer	733 lbs.	\$2,455		
PREFIX	OPTIONAL					
EG	Euro-Global Mount instead of Skid Steer Mount (factory w	velded)		\$115		
JD	JD Mount instead of Skid Steer Mount (factory welded)			\$115		
114	Prices and specifications subject to change without notice. Check discounts & availability before quoting. Product Designs May Differ Slightly Than What Appears in the Photographs.					

## SNOW REMOVAL OF STATE

### COMPACT SNOW BLADE

- ◊ Standard Universal Skid Steer Mount
- ◊ Reversible & Replaceable Rubber Edge
- ◊ Hydraulic Angle Left or Right
- ◊ Spring Loaded & Automatic Trip
- Available Sizes: 60", 72", 84" & 96"

### ORDER BLADE AND DESIRED EDGE KIT.



Model	Description	Mount	Weight Ibs.	List Price	Packed			
SNOW BLADE WITHOUT EDGE								
CSP60NE	Compact Snow Blade 60"	Uni. Skid Steer Hitch	517	\$1,755	1			
CSP72NE	Compact Snow Blade 72"	Uni. Skid Steer Hitch	537	\$1,865	1			
CSP84NE	Compact Snow Blade 84"	Uni. Skid Steer Hitch	556	\$1,970	1			
CSP96NE	Compact Snow Blade 96"	Uni. Skid Steer Hitch	587	\$2,185	1			
JDCSP60NE	Compact Snow Blade 60"	JD Hitch	517	\$1,755	1			
JDCSP72NE	Compact Snow Blade 72"	JD Hitch	537	\$1,865	1			
JDCSP84NE	Compact Snow Blade 84"	JD Hitch	556	\$1,970	1			
JDCSP96NE	Compact Snow Blade 96"	JD Hitch	587	\$2,185	1			
RUBBER EDGE								
CSP60RE	60" Rubbe	r Edge kit		\$175				
CSP72RE	72" Rubbe	ě		\$200				
CSP84RE	84" Rubbe	r Edge kit		\$225				
CSP96RE	96" Rubbe	r Edge kit		\$250				
STEEL EDGE								
CSP60SE	60" Steel Edge kit			\$125				
CSP72SE	72" Steel Edge kit			\$140				
CSP84SE	84" Steel Edge kit			\$155				
CSP96SE	96" Steel Edge kit \$170							
OPTIONAL EQUIF	PMENT							
CSP-HYD	Hydraulic angling I	Kit for CPS Model		\$625				

## SNOW REMOVAL

### SERIOUS DUTY SNOW PUSHER

- Serious Duty Construction makes this a great tool for Snow as well as Manure, etc.
- Rubber Edges come standard
- Available Sizes: 84", 96" & 120"
- Standard Universal Skid Steer Mount
- Optional JD or Euro/Global Mounts





### SERIOUS DUTY SNOW BLADE

- Reversible & Replaceable8" x 1/2" Steel Cutting Edge
  - Optional Rubber Edge 6" x 1" (reversible)
- Adjustable Blade Height

 $\Diamond$ 

 $\Diamond$ 

- Hydraulic Angle Left or Right 2" x 8" tie-rod cylinder
- Spring Loaded & Automatic Trip
- 3" x 3" x 1/4" solid backing across blade for protection and durability
- ♦ 5 1/2" thick back braces
- **o** Standard Universal Skid Steer Mount
- Optional JD or Euro/Global Mounts
  - Available Sizes: 72", 84", 96" & 108"

Model	Description	Mount	Weight	List Price			
SNOW PU	SNOW PUSHER						
XSP84	Serious Duty Snow Pusher - 84"	Universal Skid Steer	835 lbs.	\$3,565			
XSP96	Serious Duty Snow Pusher - 96"	Universal Skid Steer	895 lbs.	\$3,845			
XSP120	Serious Duty Snow Pusher - 120"	Universal Skid Steer	1,115 lbs.	\$4,595			
SERIOUS I	DUTY SNOW BLADE						
SP72	Serious Duty Snow Plow - 72"	Universal Skid Steer	820 lbs.	\$3,515			
SP84	Serious Duty Snow Plow - 84"	Universal Skid Steer	845 lbs.	\$3,645			
SP96	Serious Duty Snow Plow - 96"	Universal Skid Steer	896 lbs.	\$3,775			
SP108	Serious Duty Snow Plow - 108"	Universal Skid Steer	948 lbs.	\$3,995			
PREFIX	OPTIONAL						
EG	Euro-Global Mount instead of Skid Steer Mount (factory welded)						
JD	JD Mount instead of Skid Steer Mount (factory welded)			\$115			
<b>RE12</b>	Rubber Edge for Snow Plows (priced per foot)						

116

## MISCELLANEOUS



### **BOLT-ON TOOTH BARS**

- ◊ Convert a Smooth Edge Bucket into a Tooth Bucket
- Achieve Better Digging Power
- ◊ 1/2" x 4" Cutting Edge
- ◊ Large Pin-On Teeth (Side Pin)
- 2 Pieces of 3" Square 3/8" Thick, Pre-Drilled Steel Comes with Every Tooth Bar
- ◊ Various Size Available Upon Request Priced Per Foot, Round Up to Nearest Foot



## **BOTB SERIES**

### **QUICK ATTACH PLATES**

- Veld-On Universal Skid Steer Plates
- ◊ Available in 3 Thicknesses:
- ◊ Standard Duty 1/4"
- ◊ Heavy Duty 3/8"
- ◊ Serious Duty 1/2"

### ADAPTER BRACKETS

QA SERIES

- EG2SS Adapts Euro/Global loader mounts to universal Skid Steer mount
- JD2SS Adapts JD loader mounts to universal Skid Steer mount
- ◊ BA2SS Blank Adaptor to universal Skid Steer



Model	Description	List Price
OOTH BARS (OT	HER SIZES AVAILABLE UPON REQUEST)	
BOTB60	Bolt-On Tooth Bar - 60"	\$560
BOTB72	Bolt-On Tooth Bar - 72"	\$620
BOTB84	Bolt-On Tooth Bar - 84"	\$760
UICK ATTACH P SSQA14	Standard Duty Quick-Attach Plate - 1/4"	\$295
SSQA14	Standard Duty Quick-Attach Plate - 1/4"	\$295
SSQA38	Heavy Duty Quick-Attach Plate - 3/8"	\$375
SSQA38 SSQA12	Heavy Duty Quick-Attach Plate - 3/8" Serious Duty Quick-Attach Plate - 1/2"	\$375 \$455
-	Serious Duty Quick-Attach Plate - 1/2"	-
SSQA12	Serious Duty Quick-Attach Plate - 1/2"	-
SSQA12 DAPTER BRACK	Serious Duty Quick-Attach Plate - 1/2" ETS	\$455

## MISCELLANEOUS 😂 🔛

### MANURE FORKS

- A Replaceable Tines
- ◊ Standard Universal Skid Steer Mount
- Optional JD or Euro/Global Mounts





### TRAILER MOVER

- Great For Moving Gooseneck or Tow-Behind Trailers Around
- Standard Universal Skid Steer Mount

Model	Description	Mount	Weight	List Price				
TRAILER M	TRAILER MOVER							
XTM1	Trailer Mover	Universal Skid Steer	45 lbs.	\$595				
XTM2	Trailer Mover w/ Ball	Universal Skid Steer	134 lbs.	\$650				
MANURE F	MANURE FORK							
MF60	Manure Fork - 60"	Universal Skid Steer	391 lbs.	\$1,705				
MF72	Manure Fork - 72"	Universal Skid Steer	445 lbs.	\$1,965				
PREFIX	OPTIONAL							
EG	Euro-Global Mount instead of Skid Steer Mount (factory welded)			\$115				
JD	JD Mount instead of Skid Steer Mount (factory welded)							

# MINI SKID-STEER ATTACHMENTS





Model	Description	Misc. Info	Mount	Weight	List Price
PALLET FORKS					
TRMPF36	Pallet Forks – 36"	900# Capacity	Mini Skid Steer	251 lbs.	\$685
TRMPF42	Pallet Forks – 42"	900# Capacity	Mini Skid Steer	261 lbs.	\$705
GRAPPLES					
TRMRTG44	Root Grapple — 44"	Pioneer Fittings	Mini Skid Steer	362 lbs.	\$1,405

## MINI SKID-STEER ATTACHMENTS





Model	Description	Misc. Info	Mount	Weight	List Price		
BUCKETS							
TRMLB44	Low Pro Bucket – 44"	.22 <sup>3</sup>	Mini Skid Steer	283 lbs.	\$625		
TRMLBT44	Low Pro Bucket w/ Teeth – 44"	.22 <sup>3</sup>	Mini Skid Steer	303 lbs.	\$795		
TRMMB48	Mini Material Bucket – 48"	.34 <sup>3</sup>	Mini Skid Steer	335 lbs.	\$715		
BRUSH CUTTER	BRUSH CUTTER						
TRMBC	Brush Cutter 44"	14-25 GPM, Pioneer Fittings 4" cut capacity	Mini Skid Steer	643 lbs.	\$5,295		

## LIFT-SAFE IMPLEMENT HANDLER

Put down the chains and make moving and loading equipment a SAFE one-man job.

Belco Resources Equipment's Implement Handler was developed to make moving three point implements simple and worry free. The days of using chains and two people just to move a single rotary cutter, rear blade, landscape rake, etc. are over!

With only one person, you can safely move most three point implements quicker, safer and easier.





### **Specifications:**

- ♦ Fits most three point implements
- Lift Capacity 2,000 lbs.
- ◊ Weight 241 lbs.



**Run Forks In** 



Lift to Hook



Lower to Load

Model	Lift Capacity	Hitch	Weight	List Price
GSC-002	2,000	Cat 0, 1, 2 & 3	241	\$795

# LINITED WARRANTY TAR RIVER

Belco Resources Equipment warrants to the original purchaser of any new piece of machinery from Belco Resources Equipment, purchased from an authorized Belco Resources Equipment dealer, that the equipment be free from defects in material and workmanship for a period of one (1) year for non-commercial, state, and municipalities' use, ninety (90) days for commercial use from date of retail sale. The warranty for rental purposes is thirty (30) days. The obligation of Belco Resources Equipment to the purchaser under this warranty is limited to the repair or replacement of defective parts.

Replacement or repair parts installed in the equipment covered by this limited warranty are warranted for ninety (90) days from the date of purchase of such part or to the expiration of the applicable new equipment warranty period, whichever occurs later. Warranted parts shall be provided at no cost to the user at an authorized Belco Resources Equipment dealer during regular working hours. Belco Resources Equipment reserves the right to inspect any equipment or parts which are claimed to have been defective in material or workmanship.

This limited warranty does not apply to and excludes wear items such as shear pins, tires, tubes knives, blades, or other wear items. Oil or grease is not covered by this warranty.

All obligations of Belco Resources Equipment under this limited warranty shall be terminated if:

- Proper service is not performed on the machine.
- The machine is modified or altered in any way.
- The machine is being used or has been used for purposes other than those for which the machine was intended.

### DISCLAIMER OF IMPLIED WARRANTIES & CONSEQUENTIAL DAMAGES

Belco Resources Equipment obligation under this limited warranty, to the extent allowed by law, is in lieu of all warranties, implied or expressed, including implied warranties of merchantability and fitness for a particular purpose and any liability for incidental and consequential damages with respect to the sale or use of the items warranted. Such incidental and consequential damages shall include but not be limited to: transportation charges other than normal freight charges; cost of installation other than cost approved by Belco Resources Equipment; duty; taxes; charges for normal service or adjustment; loss of crops or any other loss of income; rental of substitute equipment, expenses due to loss, damage, detention or delay in the delivery.

#### REGISTRATION

The online Warranty Registration must be completed in order to qualify for coverage on this Limited Warranty. Visit <u>www.BR-Equipment.com</u>, click on "Warranty Registration" and completely fill out the form to register the new piece of equipment.

#### EXTENDED WARRANTY

A two (2) or four (4) extended Gearbox Limited Warranty is provided for certain models at the end of the standard one (1) year warranty period. Extended Warranty does not cover labor or freight.

#### ITEMS NOT COVERED

1. Owner Responsibility Parts: Some items must be serviced

and/or replaced because of normal machine usage. These are defined as "OWNER RESPONSIBILITY" items.

• **"V" Belts** – "V" belt service life varies due to application and conditions, such as:

Sandy abrasive conditions, slippage, burning due to overloading, improper adjustment, and engagement, etc. Thus, the service of a "V" belt may be measured in days to years. "V" belt replacement is normally an owner's responsibility.

- Ground engaging and Cutter Parts (including tines, mower blades, wear plates, guide wheels, etc.) These parts are subject to wear, abuse, and replacement. Service life of these parts can vary from hours to years. The replacement of this category of parts is the owner's expense.
- **Tires** Tires are matched to the normal operation of the machine. Excessive road use, abrasive field conditions, obstacles, improper inflation, etc. will drastically effect service life. Therefore, repair or replacement of tires is the owner's expense.
- PTO's PTO shafts are exposed to numerous conditions that the manufacturer has no control over. From the startup of a new machine, it is critical that they be "sized" to the specific tractor that the machine is being attached to. This must be the responsibility of the owner, with the aid and advice of the dealer. Many dealers take this responsibility as part of the sales process; however, the owner must be aware of this issue in switching implements between tractors. Proper angle of operation is as critical as "sizing". Improper alignment will quickly damage a PTO shaft. Running a PTO during a sharp turn can cause serious damage. Machine to tractor PTO shafts are an owner's responsibility and are not a warranty item.
- Failure due to abusive usage, lack of maintenance or accident: All repairs are the owner's expense for failures resulting from abusive usage, lack of maintenance, and/or accident.
- 3. Failures due to unauthorized alteration of machine or installation of unauthorized attachments: The installation of unauthorized attachments or the unauthorized alteration of a machine may overload certain components and result in unexpected repairs or overhaul. Any failure from the above is at the owner's expense.
- 4. Tractor Loader Attachments designated in PriceBook as "Tractor Loader Only" WILL NOT qualify for warranty if used on a SKID STEER.



## **LIMITED WARRANTY**

S3 Delta Harrows Inc. warrants that all Equipment purchased from an authorized S3 Delta Harrows Inc. Dealer in the United States or Canada shall be free from defects in workmanship and materials for a period of two (2) years from the date of purchase ("Warranty Period").

The Warranty described herein is provided by S3 Delta Harrows Inc. to the original purchaser of the Equipment from an authorized S3 Delta Harrows Inc. Dealer. The Warranty is transferable during the Warranty Period provided the authorized Dealer from which the Equipment was purchased is notified in writing within ten (10) days of the change in ownership, the transferee provides the Dealer proof of purchase from the original purchaser, and the transfer is approved by S3 Delta Harrows Inc..

S3 Delta Harrows Inc., at its option, will repair or replace any part covered by the Warranty in the previous section during the Warranty Period on the following conditions:

- (a) The End User shall notify the Dealer of the defect within thirty (30) days of failure;
- (b) The End User shall produce proof of purchase together with photographs or such other proof of failure as may be requested by S3 Delta Harrows Inc. or the Dealer;
- (c) Any Warranty repairs shall be performed by the authorized selling Dealer or other Dealer approved by S3 Delta Harrows Inc.; and
- (d) S3 Delta Harrows Inc. determines in its sole and absolute discretion that the defect or failure is covered by the Warranty.

Warranty repairs or replacement shall be free of charge to the End User for materials, labor and shipping in Year 1 of the Warranty Period. S3 Delta Harrows Inc. shall repair or replace any parts under Warranty in Year 2, but the End User shall be responsible for labor and shipping charges in Year 2.

#### NOT COVERED BY WARRANTY

S3 Delta Harrows Inc. shall not be responsible for the repair or replacement of:

- (a) Defective parts or subassemblies incorporated in Equipment that are warranted under original manufacturing warranties from OEM or third party suppliers;
- (b) Equipment that has been altered or modified in any manner not approved or authorized by S3 Delta Harrows Inc.; or
- (c) Damage caused by normal wear and tear, lack of reasonable and proper maintenance, failure to follow operating instructions in the Operator's Manual furnished with the Equipment, misuse or excessive use, or damage caused by accident, vandalism or Act of God

#### **CUSTOMER RESPONSIBILITIES**

In order to benefit from the Warranty set out herein, the End User must:

- (a) Notify the Dealer of the defect within thirty (30) days of failure;
- (b) Produce proof of purchase together with photographs or such other proof of failure as may be requested by S3 Delta Harrows Inc. or the Dealer;
- (c) Retain the defective part or subassembly for a minimum of ninety (90) days following notification of failure to the Dealer and return the defective part or subassembly to the Dealer if so requested at any time during the ninety (90) day retention period. Failure to return the part or assembly to the Dealer within thirty (30) days of request by S3 Delta Harrows Inc. may result in disallowance of the Warranty claim (if no request for return of the defective part or sub-assembly).



# LIMITED WARRANTY

#### WARRANTY AGREEMENT PROCEDURE

Liability for Defects

ENOAGRICOLA ROSSI Srl, in its capacity of manufacturer of ENOROSSI Products shall be liable for any material and/or manufacturing defects or faults of the ENOROSSI Products according to the terms and conditions of this clause (hereinafter referred to as the "Warranty").

The Warranty is for a term not to exceed 12 (twelve) months from the date on which said products are delivered to the first end user.

The Warranty is limited to the parts of ENOROSSI Products manufactured by ENOROSSI (either directly or through other companies of the group to which it belongs).

**1.1.** Within the above stated time-limits, the Warranty shall apply according to the following limitations.

- i) The Warranty shall not apply if Distributor had failed to comply with its obligations provided for under this article, or if ENOROSSI Products have been used in any other way than those ones indicated in the instructions supplied by ENOROSSI or they have been repaired, assembled, dismantled or adjusted by unauthorized persons, or if the damage is due to the use of components manufactured by third parties and not approved by ENOROSSI, or due to the use of farming or non-farming equipment that was not connected correctly and in any case not approved previously by ENOROSSI, as well as in case such changes have been made without ENOROSSI's written approval.
- ii) The Warranty does not cover damages due to force majeure, to the use of lubricants which are not suitable for the purpose or in any case do not comply with the instructions and guidelines set forth in the "Manual for Use and Maintenance" of ENOROSSI Products; damages due to overloading are expressly excluded as well.
- iii) Any obligation of ENOROSSI under the Warranty shall in no case exceed the ex-works value of the material and therefore does not include labour cost, transfer or similar charges. Materials subject to usual wear and tear, pipes, filter parts, belts, etc., are not covered by the Warranty.

1.2. In any case, Distributor undertakes to supply to the Customer at least the same form of warranty as provided for hereunder, starting from the date of delivery of the ENOROSSI Products to the firs end user, and this for the minimum period required by laws in force in the territory defined in the Agreement, without any further costs, expense or obligation of ENOROSSI than those ones defined above. Distributor shall remain liable for any warranty delivered to the Customer, irrespective of any expiration of the Warranty.

1.3. Prior to delivery to Customers, ENOROSSI Products shall be checked and tested (at Distributor's expenses) in order to eliminate possible inconveniences that might have occurred during transportation or shipment. By the time of delivery to Customers, ENOROSSI's instructions shall be given in detail and carefully to the Distributor with respect to maintenance and use of such ENOROSSI Products. The Distributor shall also, at its own expenses, carry out the first and second service to the first end user.

1) For each ENOROSSI Product, a REGISTRATION FORM Certificate shall be supplied by ENOROSSI (PDF) printed form (see Annex no. 1 RF).

Upon delivery of ENOROSSI to the Customers, the Distributor must shall:

- i) duly fill in the REGISTRATION FORM
- print the duly filled REGISTRATION FORM, sign it and have it signed by the first end user as acceptance of ENOROSSI product and as acknowledgement of all use and maintenance instructions given to the first end user; sending a copy to : service@enorossi.it
- iii) carefully keep the signed copy of the REGISTRATION FORM, for 5 (five) years

2) in case the ENOROSSI Products remaining unsold for more then 12 (twelve) months after the date of the invoice issued by ENOROSSI, prior to delivery to the first end user, the Distributor shall carry out a deeply Dedicated Pre Delivery Inspection.

1.4. All claims will be rejected unless all the complete documentation set (REGISTRATION FORM, WARRANTY CLAIM FORM, PICTURES) All repairs to ENOROSSI Products during the term of this Warranty shall be made at the care of Distributor, using the required original spare parts available in its warehouse. Should the necessary material be not available, the Distributor shall order the parts to ENOROSSI.

Spare parts shall be delivered and invoiced to Distributor by ENOROSSI. After having repaired ENOROSSI Products, the Distributor shall deliver to ENOROSSI, within 15 days from the date of the service, the ("WARRANTY CLAIM FORM"), supplied by ENOROSSI (PDF) printed form (see Annex no. 2 RG).

ENOROSSI may either accept or reject such Warranty claim, at its final judgment. The WARRANTY CLAIM FORM shall be filled in all parts; Distributor shall take care of describing all technical reasons and conditions of use that requested intervention under the Warranty.

Should the Claim be accepted by ENOROSSI, the latter shall inform the Distributor delivering a statement which will contain the outcome result, within 30 (thirty) days.

Defective material, object of any Warranty claim, shall remain at ENOROSSI's disposal since ENOROSSI may request, and, if necessary, such material shall be shipped to ENOROSSI plants for technical inspection. In such case, transportation costs shall be borne by ENOROSSI. Distributor may destroy the defective material, object of any claim, only upon receipt of ENOROSSI's written statement which contains the exit of the Warranty claim.

Parts replaced under the Warranty shall be reimbursed at the current gross price-list value in force at the date of the warranty request. The parts to replace will invoiced to the Distributor at 45% (forty-five per cent) on the current gross price-list value in force at the date. If the parts are in stock by the Distributor, ENOROSSI will send the part in the next shipment (container or truck with other machines/parts in order).

The distributor will invoice to ENOROSSI the part(s) at the same value of the invoice issued by ENOROSSI, plus the expenses/taxes paid by the Distributor to their customs, the Distributor must show all the details of these expenses/ taxes to ENOROSSI.

# **RPAN<sup>®</sup> LIMITED WARRANTY**

### WARRANTY STATEMENT

- The warranty period is valid for 36 months from the sale date or date of the delivery
- of the goods to the consumer. The purchase date is the date on the invoice issued on the receipt of the machine by the vendor or the manufacturer.
- The manufacturer guarantees the properties or the flawless operation within the warranty period which starts upon the delivery of the goods to the consumer. It is compulsory to work in compliance with the enclosed instructions for use.
- The warranty includes the repair or complimentary replacement of factory defective parts during the warranty period.
- After the warranty period expires, we provide servicing, replacement of spare parts and transportation for another seven (7) years. The producer is the authorized service provider at the same time.
- The warranty does not exclude consumer rights arising from the liability of the
- retailer for faults on goods. The machine's expected life time is 7 years from the date of the expiry of the warranty period. Within this period, we guarantee to provide servicing and spare parts.
- We guarantee that any faults or defects in the goods will be remedied within 45 days from the day of the claim for remedying the fault. Otherwise, we will replace the goods with a new one at the customer's request. We undertake to extend the warranty period for the time taken for servicing.
- Warranty card is valid only with the invoice!

#### WARRANTY TERMS AND CONDITIONS

If the damage to the machine or the . material used cannot be clearly attributed to a factory fault, the manufacturer has to inspect the product in order to determine the

validity of the warranty.

- If the damage to the machine or the material used cannot be clearly attributed to a factory fault, the manufacturer has to inspect the product in order to determine the validity of the warranty.
- The machine or faulty part transport costs are covered by the customer.
- The warranty does not cover damage caused by unauthorized persons or objects due to unprofessional handling, negligence, carelessness or non-observation of the operating manual provided by the supplier.
- The warranty does not cover damage incurred during the transport or damage resulting from abnormal operation or usage of the machine. Parts that are damaged due to excessive wear are not covered by the warranty.
- The warranty becomes void if the machine is repaired or damaged by unauthorized service personnel.
- After the completion of the loss event the replacement of the machine or an extension of the warranty period is excluded.
- If a repair is necessary, submit the warranty card and the original copy of the invoice to the authorized personnel. If the machine or its parts are sent for repair, enclose the aforementioned documents.
- Without the written approval of the manufacturer no one is authorized ta alter the data on the warranty card or give any oral or written approvals. No direct or indirect compensation for persons or objects will be given for damage resulting from the machine being out at operation.





401 Jeffreys Road Rocky Mount, NC 27804 www.BR-Equipment.com

STATES STATES

ELE DEL

Tel: 252-822-7140 Fax: 252-787-5855 SALES@BR-EQUIPMENT.COM